





GENERAL NOTES:

1. ALL STRUCTURAL STEEL, UNLESS OTHERWISE NOTED, SHALL BE ASTM A-36, MINIMUM YIELD STRENGTH 36,000 PSI.
2. ALL ALUMINUM MEMBERS, UNLESS OTHERWISE NOTED, SHALL BE OF ALLOY 6063-T5.
3. ALL HOLES TO BE DRILLED OR PUNCHED.
4. STEEL WELDING SHALL CONFORM TO AMERICAN WELDING SOCIETY STANDARD D1-1-80.

5. ALUMINUM WELDING SHALL CONFORM TO AMERICAN WELDING SOCIETY STANDARD D1. 2-97. ELECTRODES SHALL CONFORM TO AWS/SFA 5.10 CLASS ER4043.
6. ALL WELDING TO BE DONE AT TOLAR MANUFACTURING COMPANY, INC. FACILITY.



FRONT ELEVATION

END ELEVATION

REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED

UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN INCHES.		TOLAR Tolar Manufacturing Company, Inc. 258 Mariah Circle, Corona, CA 92879	
HOLES SIZE:	1/16"	DESCRIPTION:	ELEVATION DWG 33' AD W/ GLASS PANELS
< 1/16"	1/32"	CUSTOMER/OWNER:	NEW ORLEANS, LA
> 1/16"	1/8"	DWG NO.:	21973-00
ANGLES:	1/2"	SCALE:	1/16"
REMOVE ALL DIMENSIONS FROM SPECIFIC SHARP EDGES 1/4" MAX.		DATE:	09/01/15
THIRD ANGLE PROJECTION		DRAWN BY:	em
		DATE:	09/01/15
		DWG NO.:	21973-00
		SCALE:	1/16"
		DATE:	09/01/15
		DRAWN BY:	em