

Vieux Carré Commission Architecture Committee Meeting

Tuesday, February 22, 2022







500 St Peter

500 St Peter









500 St Peter








4 GENERAL - TAGS AND SYMBOLS

500 St Peter



T1.01



WILKINSON STREET (SIDE) QUIVERANT 2 QUADRANT 3 QUADRANT 4 NEW ROOF -PLATFORM EXISTING MECHANICAL EQUIPMENT TO REMAIN EQUIPMENT TO REMAR JACKSON SQUARE (ALEI) 0 LOWER ROOF (NOT VISIBLE FROM STREET)

GENERAL CONSTRUCTION NOTES

- IT IS THE CRISINAL CONTRACTORS REPROVISION TO TO NOTICE FAIR
 MAIN AVAILABLE AS SAUGHT TO ON INCONDACT WHIT CONTRACTOR
 MAIN AVAILABLE AS SAUGHT TO ON INCONDACT WHIT CONTRACTOR
 SOUR THOSE APPLIES THE REPROVISION OF COURT SCENE, REPRODUCTION
 PREPARATION TO OTHER WARM, REPITATION ACQUIRES THE WAVETENANCE
 OF MAIN TRANSLA OF TRAINING IN THE CHIEF THE THE COLLETION AND ACQUIRES
 THE COLLETION TO THE WAY THE COURT, THE PROPERTY OF THE COURT, THE WAY THE

- ADMENTAL MEMORITORISE, TO MAINTY AND MERGY VERYOR OF LEGISLATION OF MEMORITORISE CONTINUES AND MEMORITORISM AND MEMO
- DOMAGE TO THE DOSTRICA MODIFIES THE RESERVOIR. TOOLS SHOULD BE DOSTRICATED THE RESERVOIR WITH DECREMENTATE AND CHEMICALLY MOT ON SHARM, CHEMICAL CHEMICAL SHOULD BE CHEMICALLY MOT ON SHARM, CHEMICAL CHEMICAL SHOULD BE AND TEXTURE WHICH RESERVOIR CHEMICAL SHOULD BE SHARM WHICH HAVE A SOUTH OF THE SHARM OF THE CHEMICAL CHEMICAL SHARM MOTION HAVE A SOUTH OF THE CHEMICAL CHEMICAL CHEMICAL SHARM OF THE CHEMICAL CHEMICAL CHEMICAL SHARM OF THE CHEMICAL SHARM OF THE CHEMICAL CHEMICAL CHEMICAL CHEMICAL CHEMICAL SHARM OF THE CHEMICAL CHEMICAL CHEMICAL CHEMICAL CHEMICAL CHEMICAL SHARM OF THE CHEMICAL CHEMICAL CHEMICAL CHEMICAL CHEMICAL SHARM OF THE CHEMICAL CHEMICAL CHEMICAL CHEMICAL CHEMICAL CHEMICAL SHARM OF THE CHEMICAL CHEMICAL

PLAN LEGEND

MOS - NOT IN SCOPE

EXTERIOR COURTYARD - OFFEN TO A RIABOVE


GENERAL ROOF NOTES

- IT IS THE GININAL CONTRACTORS REPROVIDED BY TO PROTECT AND MANIFEST AS ANALOST TO GRI IN CONTRACT BIRL DOUBLE SECTOR MANIFEST AS ANALOST TO GRI IN CONTRACT BIRL DOUBLE SECTOR MANIFEST AND ANALOST BIRL DOUBLE SECTOR AND BIRL CONTRACTOR SECTOR SECTOR AND BIRL CONTRACTOR AND BIRL CONTRA

- JANCKE HE FERSTRECHMENDE STYPE, THEORESS TOTHER AND FERSTREAMENDE FOR OR OR SELET TOOLS AN INHEREMAL SHATE VALIDATE FERSTREAMENDE FOR OR OR SELET TOOLS AN INHEREMAL PART FERSTREAMENDE STYPE, TENTING, THEOREMS AND TROOP COMMENCE TO SELECT TOOLS AND OTHER STORM AND TROOP COMMENCE TO SELECT TOOLS AND THE STORM AND TROOP FOR SELECT SELECT TOOLS AND THE SELECT SELECT TOOLS AND PARTIES COST TO SELECT TOOLS AND THE SELECT SELECT TOOLS AND COMMENCE TO SELECT THE AND THE SELECT SELECT SELECT TOOLS COMMENCE TO SELECT THE SELECT SELECT SELECT SELECT SELECT SELECT TOOLS COMMENCE THE SELECT SE

ROOF MATERIAL LEGEND

KEY PLAN



PROJECT NUMBER CN20096 BRUE DATE 12/25/22

TRAPOLINPEER ARCHITECTS

F AND AIRS STORATION

ROOF REP/ AND RES

FMC UPB F BUILDING I RENOVATION AI 500 ST. PETER STREET NEW ORLEANS, LA 70116

FRENCH MARKET CORPORATION 1008 N. PETERS ST. #3 NEW ORLEANS, LA 70116 604-636-8400 TRAPOLIN-PEER

> 950 TCHOUPITOULAS ST. NEW ORLEANS, LA 70130 (504) 523-2772 www.trapolinpeer.com

NOT FOR

CONSTRUCTION

REVISION # DESCRIPTION | DATE

Company Name

Phone Number

Page 9 of 288


SITE PLAN


G0.04



500 S VCC Ar


2 OVERALL PLAN - ROOF PLAN GOOD SOME 1/97 - 1 07






500 St Peter







500 St Peter

Page 13 of 288





























500 St Peter – existing courtyard mechanical





500 St Peter – alternate options






500 St Peter – alternate options









500 St Peter – alternate options





WINDOW G







A6.03 SCALE: 3/16" = 1'-0"
































February 22, 2022



















208 Bienville








































BIENVILLE STREET ELEVATION

















THE COMMANDE OF THE PARTY OF TH
























































917 Decatur 1 DECATUR STREET FRONT ELEVATION

KEYNOTES

- 03 EXISTING ROOF-TOP PENETRATIONS で現底的AIM (神経 WORK)
- 04 EXISTING MECHANICAL EQUIPMENT TO BE RELOCATED TO ROOF
- 05 EXISTING FENCE TO REMAIN (NO WORK)
- 06 LOW SLOPE MEMBRANE ROOF
- 07 NEW SKYLIGHT
- 08 NEW ROOF HATCH
- 09 EXISTING GUTTER, ENSURE GUTTER IS SECURE TO THE ROOF FASCIA.
- 10 PARAPET
- 11 EXISTING METAL ROOF COVERED WALKWAY (NO WORK)
- 12 BALCONY
- 13 EXISTING ALLEYWAY
- 15 EXISTING WINDOW TO REMAIN. REPAIR DAMAGED SASHES AND TRIM. REGLAZE WHERE LITES ARE MISSING OR BROKEN.
- 16 EXISTING DOWNSPOUT, ENSURE DOWNSPOUT IS SECURE TO THE BUILDING.
- 17 EXISTING BOARD & BATTEN SHUTTERS, WHERE DAMAGED, REPLACE WOOD LIKE IN KIND AND PAINT. WHERE MISSING, REPLACE LIKE IN KIND, PAINT COMPLETE. REUSE ALL SHUTTER HARDWARE.
- 18 EXISTING SIGNAGE TO REMAIN
- 19 MASONRY TIE BACKS ADDED AT DECATUR ST BUILDING ELEVATION TO STABILIZE WALL. PAINT COMPLETE TO MATCH EXISTING COLOR.
- 20 EXISTING STORAGE SHED (NO WORK)
- 21 REPAIR RAIL BETWEEN ADJOINING PROPERTIES, PATH & REPAIR STUCCO, COLORS TO MATCH EXISTING
- 22 RE-FASTEN EXISTING LIGHT FIXURE TO WALL (NOTE: GRAPHIC REPRESENTATION OF LIGHT FIXTURE IS APPROXIMATE AND NOT INTENDED TO REPRESENT SIZE OF ACTUAL FIXTURE)
- 25 MASONRY PARAPET WALL BEYOND
- 26 ATTIC VENT
- 27 WOOD LINTEL
- 28 METAL FLASHING
- 29 RELOCATED EXISTING MECHANICAL EQUIPMENT
- 30 PARTY WALL TO BE REPAIRED AS PART OF WORK FOR 923 DECATUR
- 31 EXISTING DOWNSPOUT WITH SCUPPER AND CONDUCTOR HEAD, REPLACE MISSING PORTIONS OF DOWNSPOUT, MATCH EXISTING





917 Decatur 2 | REAR ELEVATION


VCC Architectural Committee

KEYNOTES

03	EXISTING ROOF-TOP PENETRATIONS TO SEE MAIN (2008) WORK)
04	EXISTING MECHANICAL EQUIPMENT TO BE RELOCATED TO ROOF
05	EXISTING FENCE TO REMAIN (NO WORK)
06	LOW SLOPE MEMBRANE ROOF
07	NEW SKYLIGHT
80	NEW ROOF HATCH
09	EXISTING GUTTER, ENSURE GUTTER IS SECURE TO THE ROOF FASCIA.
10	PARAPET
11	EXISTING METAL ROOF COVERED WALKWAY (NO WORK)
12	BALCONY
13	EXISTING ALLEYWAY
15	EXISTING WINDOW TO REMAIN. REPAIR DAMAGED SASHES AND TRIM. REGLAZE WHERE LITES ARE MISSING OR BROKEN.
16	EXISTING DOWNSPOUT, ENSURE DOWNSPOUT IS SECURE TO THE BUILDING.
17	EXISTING BOARD & BATTEN SHUTTERS, WHERE DAMAGED, REPLACE WOOD LIKE IN KIND AND PAINT. WHERE MISSING, REPLACE LIKE IN KIND, PAINT COMPLETE. REUSE ALL SHUTTER HARDWARE.
18	EXISTING SIGNAGE TO REMAIN
19	MASONRY TIE BACKS ADDED AT DECATUR ST BUILDING ELEVATION TO STABILIZE WALL. PAINT COMPLETE TO MATCH EXISTING COLOR.
20	EXISTING STORAGE SHED (NO WORK)
21	REPAIR RAIL BETWEEN ADJOINING PROPERTIES, PATH & REPAIR STUCCO, COLORS TO MATCH EXISTING
22	RE-FASTEN EXISTING LIGHT FIXURE TO WALL (NOTE: GRAPHIC REPRESENTATION OF LIGHT FIXTURE IS APPROXIMATE AND NOT INTENDED TO REPRESENT SIZE OF ACTUAL FIXTURE)
25	MASONRY PARAPET WALL BEYOND
26	ATTIC VENT
27	WOOD LINTEL
28	METAL FLASHING
29	RELOCATED EXISTING MECHANICAL EQUIPMENT
30	PARTY WALL TO BE REPAIRED AS PART OF WORK FOR 923 DECATUR
31	EXISTING DOWNSPOUT WITH SCUPPER AND CONDUCTOR HEAD, REPLACE MISSING PORTIONS OF DOWNSPOUT,

MATCH EXISTING






KEYNOTES

- 03 EXISTING ROOF-TOP PENETRAPPONSOT @REMAIN (NO WORK)
- EXISTING MECHANICAL EQUIPMENT TO BE RELOCATED TO ROOF
- EXISTING FENCE TO REMAIN (NO WORK)
- LOW SLOPE MEMBRANE ROOF
- 7 NEW SKYLIGHT
- NEW ROOF HATCH
- EXISTING GUTTER, ENSURE GUTTER IS SECURE TO THE ROOF FASCIA.
- PARAPET
- EXISTING METAL ROOF COVERED WALKWAY (NO WORK)
- 2 BALCONY
- 13 EXISTING ALLEYWAY
- EXISTING WINDOW TO REMAIN. REPAIR DAMAGED SASHES AND TRIM. REGLAZE WHERE LITES ARE MISSING OR BROKEN.
- EXISTING DOWNSPOUT, ENSURE DOWNSPOUT IS SECURE TO THE BUILDING.
- 7 EXISTING BOARD & BATTEN SHUTTERS, WHERE DAMAGED, REPLACE WOOD LIKE IN KIND AND PAINT. WHERE MISSING, REPLACE LIKE IN KIND, PAINT COMPLETE. REUSE ALL SHUTTER HARDWARE.
- 8 EXISTING SIGNAGE TO REMAIN
- 9 MASONRY TIE BACKS ADDED AT DECATUR ST BUILDING ELEVATION TO STABILIZE WALL. PAINT COMPLETE TO MATCH EXISTING COLOR.
- EXISTING STORAGE SHED (NO WORK)
 - REPAIR RAIL BETWEEN ADJOINING PROPERTIES, PATH & REPAIR STUCCO, COLORS TO MATCH EXISTING
- 22 RE-FASTEN EXISTING LIGHT FIXURE TO WALL (NOTE: GRAPHIC REPRESENTATION OF LIGHT FIXTURE IS APPROXIMATE AND NOT INTENDED TO REPRESENT SIZE OF ACTUAL FIXTURE)
- 25 MASONRY PARAPET WALL BEYOND
- 26 ATTIC VENT
- 27 WOOD LINTEL
- 28 METAL FLASHING
- 29 RELOCATED EXISTING MECHANICAL EQUIPMENT
- 30 PARTY WALL TO BE REPAIRED AS PART OF WORK FOR 923 DECATUR
- EXISTING DOWNSPOUT WITH SCUPPER AND CONDUCTOR HEAD, REPLACE MISSING PORTIONS OF DOWNSPOUT, MATCH EXISTING

917 Decatur

VCC Architectural Committee





1014 N Rampart















































SUSPENDED DECORATIVE STRINGLIGHT SYSTEMS





SOCKET, WIRE & CABLE DETAILS

Decostrings are a perfect accent lighting solution to add a personal ambience to patios, courtyards, atriums, restaurants, amusement parks and any open area. The "festoon" lighting system is typically strung between two anchorage points with optional intermediary support and electrically fed from one end. The sockets can be either symmetrically spaced or randomly spaced to sult the application. Optional shades, guards and lenses complete the architectual design.

Black phenolic, medium base UL weatherproof with hook for optional mounting.

SI	PEC	IFIC	CATI	ONS	
	LAN	APH	OLDE	R	

POWER CORD SUPPORT CABLE Wet location rated LED and incandescent medium base A, G or S style lamps LAMPS DIMMING Dimmable to 10% with ELV trailing edge type dimmers. VOLTAGE 120V system (1920 watts max load). No driver or transformer required. **ACCESSORIES** Optional brass, aluminum and acrylic shades. Consult factory for custom shades. PHOTOMETRY Bare lamp and shielded "BUG" rated .IES files available CERTIFICATION


PART NUMBER



1014 N Rampart































































































February 22, 2022







GENERAL CONDITIONS & NOTES

LUPON COMPLETION OF THE WORK CONTRACTOR FAMILL REMOVE ALL CONSTRUCTION DEFINE AND REPAIR ANY DAMAGE . SLESTITUTIONS OF EDAM, PRODUCTS OF CITIES MANUFACTURES WILL SE ACCIPIED ONLY LIFE'S WRITTEN APPROAUL If the owner or the Aschmict.

T. CONTRACTOR TO CHECK AND VEHILY ALL CONDITIONS, DIMENSIONS AND DETAILS AND REPORT ANY DISCREPANCES TO THE ARCHITECT REPORT CONTRACTOR CONTRACTORS.

I. CENTRACTOR BALL HAVE THE LETEMTE RESPONDEELTY FOR PROPER AND AGESLATE WATERPRODURES, FLASHING, AND CREATEDS OF SITE, PORCHES AND CREAT SPACE, SEE CREATINGS.

18. THE DESIGN ADECUACY AND WHILE OF MILE INSIGNATION, SHORING LEMPORARY SUPPORTED LETTER HE WILL RESPONSIBLITY OF THE GENERAL CONTRACTOR AND HAS NOT EXCHIOUT.

MISCELLANEOUS

2, NO CHANGE IN SEE OR EMERSION OF STRUCTURE, MEMBERS SHALL BE MADE WITHOUT THE WRITTEN APPROARL OF THE PROFESSIONAL OF \$100.00.

3. THE CONTRACTOR IS REPORTED FOR LIMIT OF THE ARCENT OF CONSTRUCTION LOAD IMPOSED LEGISLIFICATION.
PRAISED CONTRACTOR LOADS SHALL NOT EXCEED THE OFICIAL CAPACITY OF THE PRAISED AT THE TIME THE LOADS ARE

A DOUGHT STALK THEM DRAWING LINE THROUGH

SITE NOTES & WORK

ON DESTINATION OF THE STATE OF TREACHES DOCARNIES TO A SPEATER SITE STITMAN REQUIRED BY EPWARRIES SHALL BE FILLED TO A RECURSO LIANE, WITH COCRETE OF SAME RIS AS EMICIPIES FOR FOOTINGS.

DEMOLITION NOTES

FLOOR PLAN NOTES

A SECURIT ACCES FOR TERMITE PROTECTION

6. PAREN FLANGES ON BATTS TO BE ONEW, APPED AND STAPLED ON THE EDGE (N.). SIDE) OF STUDS

ALL WINDOWS BETALLED BY DATYTUS ENCLOSURES, LISSS THAN OF PEOM THE PLOOR WILL HAVE EMPETY GLAZING BY ACCORDANCE TO SECTION ROLLS OF THE INC. 2013 MD.

S. BILLPECT EACH PRICE OF TREATED LIMBER OR PLYMOOD AFTER DRIVING AND DISCARD DAMAGED OR ESPECTIVE

ELEVATION NOTES

ALL WINDOW AND DOOR HIADS TO BE HURSHID SERNO STRICTED OF BIOTHS AND DIVER EXTENDED THIS WITH GRUNNINGE BETAL FLASHING. FLASHING TO TWO DOWN OVER TIME IS MIRRIED AS LET TO BE FLASHED AS WELL SEED CITIES ON DELENGATION.

ALL AREAS AND SUBFACES TO MIRCH CALLINIS OR INDISTREE PROTECTION MATERIALS ARE BONG APPLIED SHALL DE DIVE AND FREE PROMISES, CRACKS, LODGE MATERIALS OR OTHER CONCERNS WHICH WOULD PROMISE AND HORSEN OF INSTRUME, NO WITE PRODUCTOR SHALL BY DOOR AT TRANSPALATION LOWER THAN NO DOWNER.

GENERAL STRUCTURAL NOTES

 THE CONTRACTOR BHALL BE REPORTED FOR ALL FINAL DIMERSIONS AND RELIEF OF THE STELETURE, INC. LONG. REPORTS ALL EXECUS CONDUCTOR AND DIMERSIONS SEPTIME. COMMISSIONS WORK. 2. THE CONTRACTOR SHALL WEREY THE LOCATION OF ALL EXISTING UTILITIES SEFORE COMMENCING ANY WORK, ANY INTERFERENCE SHALL BE SECURED TO THE ATTENTION OF THE STRUCTURAL. ENGINEER.

MOTE: IF ANY ITEMS HEREIN ARE NOT UNDERSTANDABLE OR CLEAR AS TO INTENT. THE CONTRACTORISM NOTIFY THE CHORECER OF EDOCRO FOR CLARIFICATION AND/OR SURPLEMBERS. DE DEMATICAL PROOF TO ACTUAL, MISTAL LATION.

WINDOW & DOOR NOTES

 PROMIDE MODIFICION FROM WINDSONS I DISPOSIÇOR MAZED DESTINOS WITH SELTTERE DE MOLICUT MODIO STRUCTURAL PARCES AND APPROVED ATTACHMENT HARDWAYS, IN ADDRESANCE TO SEE, FOR EXTERNO 2. GLEMIT ENCY DIAMNACS FOR ALL MINDOWS AND DOORS FOR ADCHITECTS INTROVAL PRIOR TO PARTICIPATION. NO DOORS OR WILDOWS BANAL REPRINCATED WITHOUT ARCHITECTS STAMPED APPROVAL DESHOP DRIVINGS.

MILLWORK NOTES

1. ALL MILLWOOK TO BE WART-BRAZE, UNLESS STREETING SOTIL 2. ALL CADRIETS TO BE PAINT-GRADE, URLESS OTHERWISE HOTED.

INTERIOR ELEVATION NOTES

1. SUBMIT SHOP GRAWINGS FOR ALL CARRELTS, NO CARRELTS SHALL BE FASSION TED WITHOUT ARCHITECTS STAMPED APPROVAL ON SHOP DEVARBOOK. ANY DEPARALL WILL DO PRINCO WITH DETWARL PRINCE PRIOR TO DODINGHOS FROSE PAINTING DO THAT ANY DRYMALL OCCUPATION, DUCMINICS, CTO., GAN DO NOTES AND CONSISTED BY DISPARALL CONTEXCTOR.

ALL CLOSETS, CHENCES AND STORAGE GRELITES AND PARTITIONS GHALL BE PLYMODO INTERIOR GRADE AD WITH SOL HOUSING ON EXPOSED EDGES, GHELVES BHALL BE SUPPORTED ALGNO ENDS AND BACK WITH SOLID WIDGE CONTRIBUOUS.

RECESSED - DOWNLIGHT

ELECTRICAL NOTES

2. CONTRACTOR SHALL SCHEDULE A WALK-THEOLOGYWITH ARCHITECT, DWIGH, AND INTERIOR DESIGNER TO BE CONDUCTED PRIOR TO ELOSINO OF WALLS TO ALLOW FOR THAIL PLACEMENT OF FINDRES, OUTLETS, AND SWITCHES TO BE





CORBETT SCOTT

RBETTSCOTTARONITECT.COM

NOT

FOR

CONSTRUCTION


Page 96 of 288

11.15.22 REVISION GENERAL NOTES

A 0.1

EXPLAINT PAIN OF EXPLAINT PARKHEATER STAIRS & LANDINGS REQUIREMENTS PLUMBING SYMBOLS 8**+** MECHANICAL SYMBOLS UNERGLIPPLYSIFFLEER RETURN ARE CONLIN **ELECTRICAL FIXTURE SCHEDULE** MANUE & MODEL & BULB LOCATION N - 23 DEGREEF, 2706 K, CRISE NA Integral LED, Warm White 5000K OUTDOOR CEILING PANELACK - PAINT ALL BLADES BLACK 52" CEILING FAN BLACK - PAINT ALL BLACES BLACK 4", BLACK BATTLE, WHITE TRIM (PAINTED) N - 33 DEGREE, 2706 K, CRI 66 N - 33 DEGREE, 2706 K, CRI 55 S - 17 DEGREE, 2706 K, CRI 65 N - 33 DEGREE, 2706 K, CRI 66 IMMSILED PRO IL POLDABLE HIGH DUTPUT TAPE LIGHT WISSLED FRO S. POLIDADE HIGH OUTFUT TAPELIGHT
LED PANEL - SURFACE MOUNT
CELLING PAN EALOY. PANT ALL BLADES BLACK
RECESSION LIGHT SURANDST FAN
110 CPM VERTILATION FAN WITH OLDAN CONTER
110 CPM VERTILATION FAN WITH OLD FAN CONTER
110 CPM VERTILATION FAN CONTER
110 METALUK 14FP LED 52" CEBLING PAN BLACK - PAINT ALL BLADES BLACK


ALL DRAWNOS ARE THE SOLE PROPERTY OF CORDETT SCOTT, ARCHITECT LLC. THEY ARE NOT TO BE COPIED, DISTRIBUTED, OR SOLD WITHTHOUT WRITTEN, EXPRESS CONSENT FRO




VCC Architectural Committee

740 Barracks

February 22, 2022






WALL TYPES

DEMOLITION NOTES	FLOOR PLAN NOTES			ROOM	A FINISH SCHEDL	ILE - 1st FLO	OOR		
R ALL EXTERIOR WALLS - REMOVE GYP BOPLASTER TO EXPOSE STUDS FOR ALL EXTERIOR. ALX: AXIBBES WENGINERS & ARCHITECT	1 1-HOUR FIRE RATED WALL - SEE WALL TYPES 2 MIN WO STAIR SHANDRALS	No. 101	ROOM LIMMG	PLOOR FINEH WOOD - REPLACE EXATE	WALL FINSH GYP 8D	CELING THISH CYP. SD.	CROWN	DAGE 12" BASE	COUNTERTOP NA
Moush desting while this location: remove tring casings, fillinging fotures, ectings. Let an needed woush risinds, hearth, and chimney	PROVIDE FIRE RATING AT UNDERSIDE OF STANSI WITH SIP 6FP, 9D, OR COLLINGS AND MALLS HISTALL 4" SOUND ATTENUATING EART INSULATION AT IN MALLS AROUND BATHROOMS FROMES ATTER ADDRESS AND AS	103	DIMING BITCHEN	W000 - REPLACE EXSTS W000 - REPLACE EXSTS W000 - REPLACE EXSTS	GYP BD GYP BD	GYP. SD. GYP. SD. GYP. SD.	COAE		MA
MOVE EXISTS COOR & TRIM THIS LOCATION. KEEP FOR POSSIBLE ROUSE IN NEW LOCATION MOUTH RESTORTANCE & RANGES			POWDER	WOOD - REPLACE EAST G	CYPED	GYP. SD.	NONE		STONE SLAD


A 1.1






February 22, 2022

A 1.2




		ELECTRICAL FIXTU	IRE SCHEDULE		
FEXTURE	TYPE	DESCRIPTION NOTE: NOT ALL FIXTURES TO BE USED	MANUF, & MODEL #	BULB	LOCATION
61 62 63 64 65 66 A B C D E F G H I J K	RECESSED DOWN, SHIT WALL SCHOOL CHURCH SPAN AS FLOOD LINE FOR THE PLOOD LINE FOR THE PLOOD LINE FOR THE PLOOD WILL LIGHT RECESSED - NOV. MINUS FLOOD WILL LIGHT RECESSED - NOV. MINUS FLOOD LIGHT CHURCH SCHOOL SHOW TO SHOW THE PLOOD FROM FLOOD FLOOD SHOWED LIGHT CELLING LIGHT CHURCH SHOW THE SHOWER LIGHT CELLING LIGHT CHURCH SHOW THE	MOTE: NOT ALL RUTURES TO BE USED. SOFT TEAR OPER LOCK BERSE, UNIT THAN PRIMITED DESIRED CHEMPER PROVIDED, CONTRACTOR RISTRALED COUTONS CELEBORY ARE ASSOCIATED ASSOCIATION AS	WAC LIBITING - IREG. EDT 118PHIDZWRT CHINNER FROVIZED ST CELLING FAR BLACK - FART JAL BLADES BLACK WAC LIBITING IN WE LEBER HA MAK WAC LIBITING IN STATE WAS LIBITING IN STATE FROM THE STATE PROGRESS LIBITING PROGRESS LIBITING PROGRESS LIBITING OWNER FROVIZED CHINNER STATE CHINNER STATE ORDER S	N - 30 DEGREE, 2700 K, CRI 18 NA NA Irespei LED, Warm White 3400K 2700 K CRI 38 1 2700 K CRI 30 1 N - 30 DEGREE, 2700 K, CRI 38 N - 30 DEGREE, 2700 K, CRI 30 N - 30 DEGREE, 2700 K, CRI 30 N N - 30 DEGREE, 2700 K, CRI 30 N NA NA NA 2700 K LED	EXTERIOR EXTERIOR EXTERIOR EXTERIOR EXTERIOR INTERIOR INTERIOR INTERIOR INTERIOR INTERIOR INTERIOR INTERIOR INTERIOR INTERIOR INTERIOR INTERIOR INTERIOR INTERIOR INTERIOR INTERIOR INTERIOR INTERIOR INTERIOR INTERIOR INTERIOR INTERIOR INTERIOR INTERIOR INTERIOR INTERIOR INTERIOR INTERIOR
N O	EXHAUST FAN - RECESSED LIGHT EXHAUST FAN - CEILING EXHUAST FAN - WALL MOUNTED	RECESSED LIGHT EXHAUST FAN 118 CFW WENTLATION FAN WITH CLEAN COVER 118 CFW VENTLATION FAN WITH CLEAN COVER	BROAN 744 BROAN GTKE BROAN GTKE	2756 K NA NA	INTERIOR INTERIOR INTERIOR




GAS LANTERN BOYNG CONCIONANCE FULUS MURAL PRINCIP PROJECTION R. ALTE THE PRINCIP PRINCIP PROJECTION R. ALTE THE PRINCIP P

A 1.3





February 22, 2022



FOR ALL EXTENDE WALLS - ALL LAP SIDING TO DE REMOVED A REPLACE IN-KIND

ALL EXTENDE THE YEAR CASE CANCED, REPARED, AND PAINTED

DEVOLUSIENT FRODON, IN-EARTH, AND CHAINEY

REMOVE DOSTING WINDOW THIS LOCATION, PREPARE FOR IN-FILL FRAMING OR REHINDO

NAMED

REMONE DESTING ROOF, GUTTERS & FLASHING

REMONE DESTING GABLE VENT. STORE FOR DIMEMSION FOR MEM GABLE VENT

FESTING CHIEF WALLS TO SE REPARKED. STUCCO TO SE AFFLED - SMOOTH FINISH.

EXISTING CHIEF TO SE INSTALLED OVER DOORS


AND LANDERS TO SE INSTALLED OVER DOORS.

11 RETAIN EMETHING CORNER BOARD TO DEMARGATE EMETHING CAMPLICACH.
12 CONSIGNED BOARD TO MARTIN CONTY.
13 CONSIGNED BOARD TO MARTIN CONTY.
14 CONTYRES A FOREIGN STATE.
15 CONTYRES A FOREIGN CONTY.
15 CONTYRES A FOREIGN CONTY.
16 CONTY CONTYRES AND CONTY.
16 CONTYRES AND CONTYRES AN

16 NEW VECHNICAL PLATFORM & ROOFTOP MOUNTED COMPRESSORS - SZED TED
19 MAGDARY STEPS
WOOD STEPS & LANDING
21 TARKLESS INT MATCH LIGHTER
22 TOSTITHO GARLY CHIT TO TERMIN REPAIR AS RECEED.
22 DISTITHO GARLY CHIT TO TERMIN REPAIR AS RECEED.
23 DISTITHO ACCESS TO BALACONET ON TERMIN REPAIR AS RECEED.

A 2.1











ROOFTOP EQUIPMENT LOCATIONS

A 2.2

8 3 - LOCATION B

740 Barracks


5 MECHANICAL EQUIPMENT - LOCATION B


ROOFTOP MOUNTED EQUIPMENT PROPOSED LOCATION B

6 1 - LOCATION B

7 2 - LOCATION B







VCC Architectural Committee

740 Barracks

February 22, 2022

CORBETT SCOTT

NOT FOR CONSTRUCTION

TREET

740 NEW

DATE 11.15.22 REVISION WINDOWS & DOORS

Page 106 of 288

GENERAL STRUCTURAL NOTES

GENERAL

- A. The contractor shall be responsible for all final dimensions and fit-up of the structure, including verifying all existing conditions and dimensions before commencing work. No change in size or dimension of structural members shall be made without the written approval of the professional of record.
- B. The contractor shall verify the location of all existing utilities before commencing any work. Any interference shall be brought to the attention of the structural engineer.
- C. The contractor shall be responsible for the design, placement, maintenance, etc. of any and all shoring, bracing, the backs, etc. needed to support any part of the new or existing construction during the entire construction process to ensure the safety and integrity of the structure until the necessary permanent dements are in place. The contractor is responsible for limiting the amount of construction load imposed upon structural framing. Construction loads shall not exceed the design capacity of the raming at the time the loads are imposed.
- D. Structural drawings are intended to be used with architectural, mechanical, and electrical drawings. See these drawings for exact location of all depressions, slopes, openings, penetrations, etc. Pienetrations not shown on the structural drawings shall be brought to the attention of the structural engineer.
- E. Dimensions Do not scale these drawings, use written dimensions only. Verify all dimensions at job site before commencing work and report any discrepancies. Where no dimensions are provided obtain clarification prior to proceeding with work.
- F. Omissions & Conflicts Omissions or conflicts between various elements of the construction documents should be brought to the attention of the design team. If certain features are not fully delineated in the construction documents, their construction shall be of the same character as for similar conditions that are delineated.
- G. Existing Conditions The Contractor shall verify the existing conditions and dimensions in the field. The Contractor shall report any discrepancies between the drawings and the actual existing conditions and dimensions to the Engineer.
- H. With the exception of defects discovered by us or pointed out to us by others to date, our design and the work shown here assumes that the existing structural elements are sound and capable of supporting loads to their full, theoretical, code-allowed capacities. EOR is not responsible for any additional costs, damages, or injuries resulting from discovery or failure of any element that is found to be damaged, deteriorated, or otherwise structurally impaired.
- The Contractor shall inform the professional of record in writing of any
 deviation from the Contract Documents. The Contractor shall not be relieved of the
 responsibility of such deviation by the professional of record review of shop
 drawings, product data, etc., unless the contractor has specifically informed the
 professional of record of such deviation at the time of submission, and the
 professional of record has given written approval to the specific deviation.
- Note: if any items herein are not understandable or clear as to intent, the contractor must notify the Engineer of Record for clarification and/or supplemental information prior to actual installation.

II. DESIGN BASIS

Applicable Codes and Standards
 International Residential Code 2015: ASCE 7-2010

B. Design Loads

KOOT			
Live Load	20 psf;	Dead Load	10 psf
Decks			
Live Load	60 psf;	Dead Load	10 psf
Living Floors			
Live Load	40 psf	Dead Load	10 psf

Wind Load
The criteria is based on ASCE 7-2010 Minimum Design Loads for Buildings and Other
Structures:

Basic Wind Velocity 145 mph

Risk Category II

Exposure B

For Main Wind Force Resisting System - Enclosed Building, Method 1, Simplified Procedure

For Components and Cladding - Partially Enclosed Building, Method 2, Analytical Procedure

C. Deflection Limitations

C. Deflection Lin Floor Members Live L/360

Dead + Live

Roof Member Roof Live L/240

III. MATERIALS

Call before you dig.

F. WOOD FRAMING

All wood framing fabrication and erection shall conform to the National Design Specification for Wood Construction by the NFPA, the Plywood Design Specification by the APA and meet the requirements below. Unless noted otherwise, all wood connections shall be in accordance with the fastening schedule of the International Residential Code.

All lumber or plywood in contact with masonry or exposed to earth or weather shall be pressure treated with CCA or MCQ to a minimum retention of 0.40 LBS/CU. FT. in accordance with AWPA. ACQ treatment is not allowed without written approval of the structural engineer. All treated wood members shall be connected or fastened with galvanized nails, screws, or oblist. The coating must be hot-dipped to an equivalent of 6-90 rating or greater.

Framing Lumber - Southern Yellow Pine grade marked and kiln dried, S4S, No. 2, maximum moisture content 19%. All member piece ends, joints, or splices shall be over supports unless noted otherwise. Studs shall be continuous between floor

Unless noted otherwise multiple pieces of lumber used to form beam or header members shall be attached together with 4 rows of 16d nails spaced at 16° for pieces up to 12° deep, 5 rows of 16d nails at 16° for pieces 14° and 16° deep and 6 rows of 16d nails spaced at 16° for pieces 18° deep.

Openings

All openings in exterior wood-framed walls shall have the following minimum number of studs at each jamb:

Openings larger than 10"-0"....See Plan or consult Struct. Eng.
Unless shown otherwise all openings in wall shall have headers consisting of a
minimum of two 2x12x.

Floor Framing - Provide bridging for dimensioned lumber floor joists at 8'-0" o.c.

Plywood Flooring - APA rated 48/24, 3/4" thick. Nail with 12d nails spaced at 6" o.c. at panel ends and 12" o.c. at intermediate supports.

Plywood Roofing - APA rated 32/16, 5/8" thick. Nail with 10d nails spaced at 6" o.c. at panel edges and 12" o.c. at intermediate supports.

Plywood Wall Sheathing - Provide 1/2" plywood on all the exterior walls to brace the structure for wind loads. Unless shown otherwise all plywood sheathing shall be fastened with 8d ring shank nails (.131" min. diameter) or #10 screws (.19" nominal diameter) spaced at 6" o.c. maximum along supporting members on the interior or each sheet and spaced at 4" o.c. maximum along supporting members at the edges of each sheet. The use of staples will not be allowed. All plywood wall sheathing shall have solid blocking at all horizontal joints. Vertical joints of plywood roof sheathing shall be staggered every four feet or less.

LVI. Members - All members designated as "IV.I." shall be laminated veneer lumber having properties and strength equal to Trus Joist "Microllam" with a minimum designated modulus of elasticity of 2000 ksi (2.0E) for all headers and beams. LVL members shall be glued and nailed together following the manufacturer's


GRAPHIC LEGEND



ABBREVIATIONS

0	AT
CMU	CONCRETE MASONRY UNI
EA.	EACH
GALV	GALVANIZED
GEN	GENERAL
NEN	MINISHUM
0.0	ON CENTER
PT	PRESSURE TREATED
TVP	TYPICAL









231 Royal Street






























231 Royal Street





231 Royal Street

February 22, 2022










5 EXISTING STOREFRONT DOOR DETAIL N.T.S.

4 EXISTING VIEW ROYAL ST. EXIT N.T.S.

- REMOVE AND SALVAGE THE EXISTING END PANEL.


3 EXISTING STOREFRONT N.T.S.

2 EXISTING VIEW FROM ROYAL ST. N.T.S.























VCC Architectural Committee

February 22, 2022



















1130 Chartres

GENERAL NOTES

- The contractor shall confirm and verify in writing (employ surveyor) that all property lines and setbacks are met prior to the start of construction.
- The contractor shall coordinate and obtain all necessary permits and approvals from authorities having jurisdiction. Construction work is not to begin until all required regulatory approvals have been issued.
- All materials and work shall be in accordance with current applicable federal, state and local building codes, amendments, rules, regulations, ordinances, laws, orders, and approvals that are required by public authorities having jurisdiction over the work. In the vent of conflict, the most stringent requirements shall apply. No work shall be concealed until approved by local inspectors
- It is the intent of the contract documents to provide for complete and finished work. Each trade (subcontractor) shall completely review plans for their respective work and related work by other trades (subcontractors). The contractor shall coordinate and provide all miscellaneous components and parts which are not shown on the contract documents but are required to complete the work shown. Incidental work and components which are required as an essential, functional or operational item or system, are required to complete any assembly and to complete full scope of work.
- The contractor shall subcontract with suppliers, fabricators, and installation companies which can demonstrate that they possess the knowledge, experience and proven capabilities to fully perform all aspects of work without omission
- All products shall be installed in compliance with industry standards and as required by the oduct manufacturer's latest published specifications and installation req
- The contractor shall protect all materials, construction, utilities and facilities from damage, including workers, thatt and weather. Damaged components shall be replaced at no cost to Owner.
- All pipe chase walls shall be constructed to completely conceal and enclose pipes with full hickness of gypsum board on each side of the wall.
- The contractor shall install and provide all safety barriers during construction to protect the public from injury and access to the building and site.
- 0. Fire rated assemblies shall be constructed in compliance with published UL Certifications Directory Listings and Classifications and shall be in accordance with continuoutity diagrams. Joints occurring in fire rated assemblies (walls and ceilings) shall be staggered both horizontally and vertically
- Substitutions must be pre-approved in writing by architect prior to the start of construction.
 Any work or material requirements of such substitution shall be coordinated (with all trades) and provided by the contractor. Contractor must verify in writing all substitutions will not impact project cost or project schedule prior to request of such substitution. Substitutions shall be approved by regulatory agencies in writing prior to the start of construction.
- 12. The contractor and subcontractors shall review and coordinate all architectural, electrical and mechanical work to confirm that all components will achieve their intended use an will maintain ceiling heights shown. Conflicts shall be brought to the attention of the architect
- Asbestos abatement, lead paint removal, and other hazardous material removal is not in the contract. Should the contractor encounter the presence, or possible presence, of potentially hazardous materials, the contractor shall notify the owner for instructions prior to
- 14. Safety measures: at all times, the contractor shall be solely and completely responsible for the conditions of the job site, including the safety of persons and property, and for all necessary independent reviews of these conditions. The architects, engineers, or owner's job site review is not intended to review the adequacy of the contractor's safety measures
- 16. The contractor shall not submit final price or execute contract with Owner until all required changes requested by the regulatory agencies have been included in the contract price
- 16. Buildings shall be maintained in weatherproof and secure condition as early as possible
- 17. Erect and install all work level, plumb, square, true, straight and in proper alignment.
- 18. The contractor shall be responsible for field verifying actual locations of all existing utilities and structures on the project site. Locations of existing utilities and structures indicated on the drawings are approximate only, and those indicated are not necessarily all that may exist on the project site. The contractor shall coordinate the location (horizontal and vertical) of the existing utilities (power, telephone, gas, water, sewer, etc.) with the appropriate utility provider before construction begins and at no additional cost to the
- 9. All existing sanitary sewer manhole tops, water valve boxes, meters, storm sewers, or other related appurtenances shall be adjusted to finish grade by contractor at no additional
- 20. When project is complete, clean and polish glass, hardware, and other such items with factory finishes. Remove all dust with freated dust collines or vacuum cleanners. Waste and refuse caused by the work shall be removed from premises and disposed of by contractor. Glasn site at one of project. Remove dust, daths, sits, stains, fingarprints, and labels from exposed surfaces, including glazing.
- 21. Furniture is for reference only. Furniture is not in project scope. Furniture, fixtures and equipment (FFE), if required, will be submitted in a separate design package.
- 22. Do not scale drawings for field layout. Contact architect if dimensions are needed and cannot be found in drawing set.
- Floor plan dimensions taken from face of stud or centerline of stud / column unless otherwise noted. "Clear" refers to dimension between faces of finish surfaces, "EQ" or "Equal" indicates dimension to match adjacent. Lettered dimensions (A,B,C,D,ETC) indicate dimension to match opposite or remote (matching letter) dimension. "*-" indicates approximate dimension based on field constition or flexible dimension that can be adjusted.
- 24. All dimensions on reflected ceiling / lighting plans are clear dimensions
- 25. These drawings are accompanied by the Project Manual



SITE / VICINITY PLAN

OWNER

Soniat Holdings, LLC.

1133 Chartres St.

New Orleans, LA 70116

ARCHITECT

Albert Architecture and Urban Design, aplic

Richard Albert 3221 Tulane Avenue New Orleans, LA 70119 504.827.0056

INTERIOR DESIGNER

Ken Fulk

310 Seventh St. San Francisco, CA 94103 415.285.1164

GENERAL CONTRACTOR

Entablature

8438 Oak St., Suite C New Orleans, LA 70118 504.322.3822

MECHANICAL

Albert Engineering

Michael Leitzinger 3221 Tulane Avenue New Orleans, LA 70119 504.827.0056

ELECTRICAL

King Consulting Engineering, LLC

Kerwyn King P.O. Box 870398 504.399.1141

SONIAT HOUSE

SONIAT HOLDINGS, LLC. 1130, 1133-1137 CHARTRES ST. NEW ORLEANS, LA 70116

PERMIT SET

02.07.22

DRAWING INDEX

A-5.10	ROOF JACKS / MECH PENETRATIONS	
G-0.00	COVER SHEET	
G-0.01	INFORMATION SHEET	
G-C.02	WALL FIXTURE MOUNTING AND ADA STANDARDS	
G-0.03	SURVEY	
0.004	Maria A Therefore	

G-0.04 WALL TYPES
LS-1.00 LIFE SAFETY - FIRST FLOOR
LS-1.01 LIFE SAFETY - SECOND FLOOR
LS-1.02 LIFE SAFETY - THIRD FLOOR INTERIOR DEMO-FIRST FLOOR-1133-1137 CHARTRES

INTERIOR DEMO-FIRST FLOOR-1133-1137 CHARTERS
INTERIOR DEMO-FIRST FLOOR-1130-0 WRITES
INTERIOR DEMO-SECOND FLOOR-1133-1137 CHARTERS
INTERIOR DEMO-SECOND FLOOR-1133-1137 CHARTERS
INTERIOR DEMO-FIRST FLOOR-1135-1137 CHARTERS

A-1.02 A-1.03 A-1.04 A-1.05 A-1.09 A-1.10 A-1.11 A-1.12 EXTERNOR ELEVATIONS

A-1.13 A-2.00 A-3.00 A-3.01 A-3.02 A-5.00 A-5.01 A-5.02 A-5.08 A-5.04 SECTIONS 3 TPO ROOF DETAILS ROOF DETAILS

A-5.05 VCC STANDARD DETAILS: IRON BALCONY AND GATES EXTEROR GATE/DOOR DETAILS ELEVATION OF ROOF PENETRATIONS

INTERIOR FINISH SCHEDULI

FIRST FLOOR PLAN - 1123-1137 CHARTRES STREET FIRST FLOOR PLAN - 1130 CHARTINES SECOND FLOOR PLAN - 1135 - 1137 CHARTINES

SECOND FLOOR PLAN - 1133 - 1137 CHARTINES SECOND PLOOR PLAN - 1133 - 1137 CHARTINES THARD PLOOR PLAN - 1133 - 1137 CHARTINES ROOP PLAN FIRST FLOOR PLAN - ROP - 1133-1137 CHARTINES FRIST FLOOR PLAN - ROP - 1133-1137 SECOND PLOOR PLAN - ROP - 1133-1137 SECOND FLOOR PLAN - RCP - 1139 THIRD FLOOR PLAN - RCP - 1133-1137

VOC STANDARD DETAILS - BRICK AND MORTAR VCC STANDARD DETAILS, SHUTTERS VOC STANDARD DETAILS - DORMER, WINDOWS 6

WALL TYPES INTERIOR FINISH KEY PLAN

ID-1.02 INTERIOR FINISH KEY PLAN ID-1.03 INTERIOR FINISH KEY PLAN ID-1.05 INTERIOR FINISH KEY PLAN ID-1.06 INTERIOR FINISH KEY PLAN M-0.01 HVAC GENERAL NOTES AND SCHEDULES

HVAC SCHEDULES FIRST FLOOR PLAN - 1133-1137 CHARTRES FIRST FLOOR INVAC - 1130 CHARTRES FIRST FLOOR MAC - 1133-1137 CHARTRES SECOND FLOOR MAC - 1133-1137 CHARTRES THEO FLOOR MAC - 1136 CHARTRES THEO FLOOR MAC - 1135-1137 CHARTRES ROOF MAC PLAN - 1135-1137 CHARTRES

N-1.07 ROOF HVAC PLAN- 1130 CHARTRES N-2.01 HVAC DETAILS HVAC DETAILS MECHANICAL RISERS

ELECTRICAL GENERAL NOTES FIRST FLOOR ELECTRICAL PLAN 1183-137 CHARTRES FIRST FLOOR ELECTRICAL PLAN 1183 CHARTRES SECOND FLOOR ELECTRICAL PLAN 1133-1137 CHARTRES SECOND FLOOR ELECTRICAL PLAN 1130 CHARTRES E-1.03

THIRD FLOOR ELECTRICAL PLAN 1185-1137 CHARTRES ROOF ELECTRICAL PLAN 1135-1137 CHARTRES E-1.07 ROOF ELECTRICAL PLAN 1130 CHARTRES E-2.01 ELECTRICAL RISER DIAGRAM AND DETAILS

P 0.01 P-1.00 P-1.01 PLUMBING GENERAL NOTES AND SCHEDULES UNDERGROUND PLUMBING 1133-1137 CHARTRES UNDERGROUND PLUMBING 1130 CHARTRES FIRST FLOOR PLUMBING- 1133-1137 CHARTRES

FIRST FLOOR PLUMBING- 1130 CHARTRES SECOND FLOOR PLUMBING- 1120-1127 CHARTRES SECOND FLOOR PLUMBING- 1128 CHARTRES

SECOND FLOWR PLUMBING- 1138-CHARTRES
PLUMBING DETAILS
PLUMBING DETAILS
PLUMBING DETAILS
PLUMBING ISOMETRIC PLAN

Albert Architecture & Urban Design aplic

3221 Tulone Avenue New Orleans, LA 70119 504.827.0056

This drawing is crosstylted and in the noise grouping of Albert Architecture & Ultran Design and Architecture & Ultran Design and Architecture & Ultran Design and Architecture in commission. Constrained haven without the written permetation of Albert Architecture & Ultran Design applies is prohibited, all rights reserved.

SONIAT HOUSE

1130, 1133-1137 CHARTRES STREET NEW ORLEANS, LA 70116

Project No. AA2109


02.07.22

Interior Demolition Set Permit Set 05.28.21 Revised Demolition Set 12:16:21 01.27.22 Permit Revisions


G-0.00

COVER SHEET





DEMO- FIRST FLOOR - 1130 CHARTRES



GENERAL DEMOLITION NOTES

- REMOVE ALL EXISTING CARPET AND UNDERLAYMENT. TAKE CARE TO NOT DAMAGE EXISTING WOOD FLOORS BELOW REMOVE EXISTING ARCHITECTURAL LIGHTING REMOVE ALL EXISTING MILLWORK REMOVE EXISTING CROWN, CASING BASE AND WALL PANELING, TYP, HISTORIC MOULDING TO BE CAREFULLY REMOVED AND STORED ON SITE.

GRAPHIC LEGEND - DEMOLITION INDICATES AREA NOT IN SPECIFIC PHASE'S SCOPE OF WORK EXISTING WALLS, PARTITIONS, COLUMNS, FIXTURES, EQUIPMENT, ETC. TO REMAIN EXISTING WALLS, PARTITIONS, COLUMNS, FIXTURES, EQUIPMENT, ETC. TO BE REMOVED

© 2022 Albert Architecture & Lithen Design or lic

ARCHITECTURE

3221 tolene Avenue New Orleans, LA 70119 Page 128 of 288 504.827.0056

This drawing is copyrighted and is the sole property of Albert Anchinecture & Uttan Design agin. Any use or reproduction of this drawing or the information contained herein without the written permission of Albert Architecture. & Uttan Design agilo is prohibited, all rights reserved.

SONIAT HOUSE

1130, 1133-1137 CHARTRES STREE NEW ORLEANS, LA 70116


Project No. AA2109

Permit Revisions


D-1.01

INTERIOR DEMO-FIRST





DEMO - SECOND FLOOR - 1130 CHARTRES



GENERAL DEMOLITION NOTES

1. DOOSE, FAMEE, MIC CAPIGS RUCCHED FOR REMOVE TO BE SALVANCE, STOKEL AND PROTECTED FOR REMOVE TO BE SALVANCE, STOKEL AND PROTECTED DURING TO REMAIN AND TO BE COVERED NO PROTECTED DURING DEMOUT

FINANCE ALL EXETING CAPPET AND EXEMPT AND EXEMPT AND

GRAPHIC LEGEND - DEMOLITION

NOCATES AREA NOT IN SPECIFIC

PHASTES SCURE OF VERIEN

EXTENSIVE ANALS, PARTITIONS, COLLARGE,
FUNDING MALLS, PARTITIONS, COLLARGE,
EXPERISE COLLARGE, COLLARGE,
EXPERISE COLLARGE, TO, TO SE REMOVED

INTERIOR FINISHES TO BE REMOVED

@ 2022 Albert Architecture & Urban Design aplic



Page 129 of 288

3221 Tulane Av New Orleans, LA

This thereing is constituted and in the sole property of Albert Architecture 5. Uthan Design agin. Any use or reproduction of this thereing or the information contained herein without the written permission of Albert Architecture 8 Uthan Design acid is prohibited, all rights reserved.

SONIAT HOUSE


1130, 1133-1137 CHARTRES STREET NEW ORLEANS, LA 70116

Project No. AA2109

D-1.03

INTERIOR DEMO-SECOND FLOOR-1130 CHARTRES





SONIAT HOUS

1130, 1133-1137 CHARTRES NEW ORLEANS, LA 70116

Project No. AA2109

02.07.22

Drawn by: Checked by:

Revised Permit Set Revised Demolition Set

Permit Revisions

Interior Demolition Set

Permit Revisions

D-1.05

DEMO - ROOF -1130-1135


@ 2022 Albert Architecture & Urban Design apllc


Albert Architecture & Orban Design uplic

3721 Tidane Avenue New Orleans, LA 70119 504-827-0056

This drawing is congrighted and in the sone property of Albert Archhestus & Utaha Design and A. Arc use of the constitution of the Architecture & the constitution of the Architecture & Utaha permanent of Albert Architecture & Utaha Design and it is prohibited, all rights reserved.

Page 131 of 288





SONIAT HOUSE

1130, 1133-1137 CHARTRES STRI NEW ORLEANS, LA 70116

Project No. AA2109

02.07.22

38
09
11
12
91
52


SITE PLAN 1" = 10'-0"

A-1.00

SITE PLAN


© 2022 Albert Architecture & Urban Design apilic






VCC Architectural Committee

ALBERT





Project No. AA2109 02.07.22 Drawn by: Checked by: JM Interior Demolition Set 08.13.21 Permit Set 09.23.21 Revised Permit Set 11.05.21 Revised Demolition Set 12.16.21 Permit Revisions 01.27.22 02.27.22

© 2022 Albert Architecture & Urban Design aplic

A 1.00

ROOF PLAN







GENERAL RCP NOTES

- EXISTING CEILING AND LIGHTING TO REMAIN, MODIFY AS REQUIRED.
- CARBON MONOXIDE DETECTORS AND SMOKE DETECTORS TO BE INSTALLED AS SHOWN AND AS REQUIRED TO MEET CURRENT BUILDING CODE REQUIREMENTS.
- FI FETRICIAN SHALL VIRREY SWITCH LOCATIONS WITH ARCHITECT/OWNER PRIOR TO START OF INSTALLATION,
- ALL WALL-MOUNTED VANITY, PICTURE LIGHTS, SCONGES, AND DECORATIVE FORTURES TO BE LOCATED IN THE FIELD WITH ARCHITECT.
- V.I.F. ALL CENTERLINES WITH ARCHITECT IN FIELD.

SONIAT HOUSE 1130, 1133-1137 CHARTRES STREE NEW ORLEANS, LA 70116

Project No. AA2109

Dnawn by:	
Checked by:	
Interior Demolition Set	
menor Demolippin Sec	_
Permit Set	
Revised Permit Set	
Revised Demolition Sat	
Permit Revisions	
Permit Revisions	
e iii, rensons	

A-1.10

© 2022 Albert Architecture & Urban Design apilo RCP - 1130 CHARTRES

FIRST FLOOR PLAN - RCP - 1130

1130 Chartres




Albert Architecture & Orban Dasign applic 3221 Tulane Avenue New Orleans, LA 70119 New Ordens, LA 7019

Pagge 135 of 288

This clearly is copyrighted and is the ode; scoperny of other Architecture & reportation of the development of the development

FIRST FLOOR PLAN -





GENERAL RCP NOTES

- EXISTING CELLING AND LIGHTING TO REMAIN, MODIFY AS REQUIRED.
- EXISTING AND NEW, TO BE COORDINATED WITH OWNER AND
- INSTALLED AS SHOWN AND AS REQUIRED TO MEET CURRENT BUILDING CODE REQUIREMENTS.
- COORDINATE ALL RECESSED LIGHT HOUSING LOCATIONS WITH ARCHITECT IN FIELD PRIOR TO INSTALLATION TO ACCOMIDATE CENTERLINES WITH FRAMING.
- ELECTRICIAN SHALL VERIFY SWITCH LOCATIONS WITH ARCHITECT/OWNER PRIOR TO START OF INSTALLATION.
- PROVIDE SUBMITTALS OF ALL LIGHT FIXTURES, FANS, AND SWITCHES FOR ARCHITECT'S REVIEW PRIOR TO THE START OF
- ALL WALL-MOUNTED VANITY, PICTURE LIGHTS, SCONCES, AND DECORATIVE FIXTURES TO BE LOCATED IN THE FIELD WITH ARCHITECT.
- V.I.F. ALL CENTERLINES WITH ARCHITECT IN FIELD.
- 10. CONTRACTOR TO PROVIDE DESIGN (BUILD PRICE FOR COMPLETE ELECTRICAL SYSTEM ACCOMMODATING THE ILLUSTRATED LAYOUT, PROVIDE SHOP DERAWINGS FOR OWNER REVIEW PRIOR TO THE START OF CONSTRUCTION, TYP.

This drawing is copyrighted and is the sole property of Albert Architecture & Urban Design apile. Any use or reproduction of this drawing or the information contained herein without the written permission of Albert Architecture & Libran Design and is prophistical.

SONIAT HOUSE

1130, 1133-1137 CHARTRES STREE NEW ORLEANS, LA 70116

Project No. AA2109

01
00
11
12
01
02

A-1.12

SECOND FLOOR PLAN -RCP - 1130

SECOND FLOOR PLAN - RCP - 1130

© 2022 Albert Architecture & Urban Design aplic





NEW ORLEANS, LA 70116

Project No. AA2109

02.07.22

Drawn by: AP Checked by: JM

 Interior Demolition Set
 08.13.21

 Permit Set
 09.23.21

 Revised Permit Set
 11.05.21

 Revised Demolition Set
 12.16.21

 Permit Revisions
 01.27.22

 Permit Revisions
 02.27.22

Permit Revisions 02.27.23

A-2.00

EXTERIOR ELEVATIONS

NOTE:

REFERENCE GENERAL VCC GUIDELINE SHEETS (A-5.02 - A-5.05) FOR APPROVED STANDARD DETAILS. CONTACT ARCHITECT IF APPLICABILITY OF DETAIL IS IN QUESTION.

© 2022 Albert Architecture & Urban Design aplic





Drawn by: Checked by:

02.07.22

 Interior Demolition Set
 08.13.21

 Permit Set
 09.23.21

 Revised Permit Set
 11.05.21

 Revised Demolition Set
 12.16.21

 Pormit Revisions
 01.27.22

 Permit Revisions
 02.27.22

SECTIONS 2

A-3.01

© 2022 Albert Architecture & Urban Design aplic





Interior Demolition Set 11.05.21

ALBERT ARCHITECTURE

Page 139 of 288

A-3.02

SECTIONS 3 © 2022 Albert Architecture & Urban Design aplic

GUTTERS AND DOWNSPOUTS TO BE REPARTE OF REPLACED AS REQUEED, QUTTERS TO BE VCC APPROVED HALF-ROUND SYSTEM, TVP. ROOF - 1130 - 28'-2"+ CLEAN, REPAIR, AND PAINT EXISTING WINDOWS AND DOORS AS REQUIRED, TYP. WINDOWS A DOORS TO BE REGLAZED IF NECESSARY. ELECTRIC LAWPS AND WALL SCONGES TO BE REPLACED WITH NEW VCC APPROVED LAWPS, TYP. SECOND FLOOR - 1130 FIRST FLOOR


SECTION / COURTYARD ELEVATION 5 - 1130 CHARTRES
3/16* - 1'-0'


SECTION / REAR ELEVATION 6 - 1130 CHARTRES

1130 Chartres

NOTE:

REFERENCE GENERAL VCC GUIDELINE SHEETS (A-6.02 - A-6.05) FOR APPROVED STANDARD DETAILS CONTACT ARCHITECT IF APPLICABILITY OF DETAIL IS IN QUESTION.





WOOD INVILER

ROCKING PARTIES.

ONGETED PARTIES.

PARTIE

PORT ALTON OUT, BEE

RECOMMENT,

META, FURRING

SEALING MATERIAL

PRESENTED AND RECORDED

AND RECOMMENT

SEALING MATERIAL

SEALING MATERIA

ARCHITECTURE

Page 141 of 288

Allest Architecture & Olders Angere (1888)

3221 Taken Awarea
(New Climen, LA 72119

This develop is compressed and in the code properly of Albert Architecture is compressed in the code properly of Albert Architecture is compressed in the code properly of Albert Architecture is compressed in the code properly of Albert Architecture is compressed in the code properly of Albert Architecture is compressed in the code properly of Albert Architecture is compressed in the code of the code of

ALBERT

NRCA DETAIL MB-04

PICTORAL VIEW AT BASE FLASHING

PICTORAL VIEW OF BASE FLASHING AT METAL CURB

SECTION THRU ROOF AT CURB FOR DUCT PENETRATIONS

SONIAT HOUSE

1130, 1133-1137 CHARTRES STREET NEW ORLEANS, LA 70116

Project No. AA2109

TREATED PLOCHERS, AS REQUIRED
TO ANALYSE FOR S., OFE
THE CONTINUOUS CE AND WATER
AND IN CONTI

A-5.00

TPO ROOF DETAILS


PRINT SUITACE AS RECAMBED MANDROWNE FLADHEST SHEET ACHERED TO SWOODS BACKES STORT TORCH APPLED DIVISTANCE MORPHED DIVISTANCE MORPHED MANDRO STORT TORCH APPLED MANDRO STORT THE FLAD STORT SHEET THOST FOR SPILE SOURCE STREAMS FLANGE SECURITY TO WALL AND CIECK SHEET METML SCLIPPER SECURITY TO WALL AND CIECK SHEET METML SCLIPPER SECURITY TO WALL AND CIECK SHEET METML SCLIPPER

PICTORIAL VIEW AT SCUPPER

TPO ROOF EDGE DETAIL
3' + 1'.0'

© 2022 Albert Architecture & Urban Design apile










SECTION AT TPO ROOF AT EXISTING PARAPET - 1130 CHARTRES

1 1/2" = 1'-0"











2 A-5.08 3/4" = 1'-0" 1130 CHARTRES STREET ENTRY GATE





1135 Chartres







February 22, 2022












































Existing front slope skylights





GENERAL NOTES

- The contractor shall confirm and verify in writing (employ surveyor) that all property lines and setbacks are met prior to the start of construction
- The contractor shall coordinate and obtain all necessary permits and approvals from authorities having jurisdiction. Construction work is not to begin until all required regulator approvals have been issued.
- All materials and work shall be in accordance with current applicable federal, state and local building codes, amendments, rules, regulations, ordinances, laws, orders, and approvals that are required by public authorities having jurisdiction over the work. In the event of conflict, the most stringent requirements shall apply. No work shall be concealed until approved by local inspectors
- It is the intent of the contract documents to provide for complete and finished work. Each rade (subcontractor) shall completely review plans for their respective work and related work by other trades (subcontractors). The contractor shall coordinate and provide all miscellaneous components and parts which are not shown on the contract documents but are required to complete the work shown. Incidental work and components which are required as an essential, functional or operational item or system, are required to complete any assembly and to complete full scope of work.
- The contractor shall subcontract with suppliers, fabricators, and installation companies which can demonstrate that they possess the knowledge, experience and proven capabilities to fully perform all aspects of work without omission.
- All products shall be installed in compliance with industry standards and as required by the product manufacturer's latest published specifications and installation requirements.
- The contractor shall protect all materials, construction, utilities and facilities from damage, including workers, theft and weather. Damaged components shall be replaced at no cost
- All pipe chase walls shall be constructed to completely conceal and enclose pipes with full thickness of gypsum board on each side of the wall.
- The contractor shall install and provide all safety barriers during construction to protect the
- Fire rated assemblies shall be constructed in compliance with published UL Certifications Directory Listings and Classifications and shall be in accordance with continuoutity diagrams. Joints occurring in fire rated assemblies (walls and ceilings) shall be staggere
- Substitutions must be pre-approved in writing by architect prior to the start of construction.
 Any work or material requirements of such substitution shall be coordinated (with all trades) and provided by the contractor. Contractor must verify in writing all substitutions will not impact project cost or project schedule prior to request of such substitution. Substitutions shall be approved by regulatory agencies in writing prior to the start of construction
- 2. The contractor and subcontractors shall review and coordinate all architectural, electrical and mechanical work to confirm that all components will achieve their intended use an will maintain ceiling heights shown. Conflicts shall be brought to the attention of the architect prior to the start of construction.
- 13. Asbestos abatement, lead paint removal, and other hazardous material removal is not in the contract. Should the contractor encounter the presence, or possible presence, of potentially hazardous materials, the contractor shall notify the owner for instructions prior to
- 4. Safety measures: at all times, the contractor shall be solely and completely responsible for the conditions of the job site, including the safety of persons and property, and for all necessary independent reviews of these conditions. The architect's, engineer's, or owner's job site review is not intended to review the adequacy of the contractor's safety measures
- 15. The contractor shall not submit final price or execute contract with Owner until all required changes requested by the regulatory agencies have been included in the contract p
- 16. Buildings shall be maintained in weatherproof and secure condition as early as possible
- 17. Erect and install all work level, plumb, square, true, straight and in proper alignment.
- 18. The contractor shall be responsible for field verifying actual locations of all existing utilities and structures on the project site. Locations of existing utilities and structures indicated on the drawings are approximate only, and those indicated are not necessarily all that may exist on the project site. The confractor shall coordinate the location (horizontal and vertical) of the existing utilities (power, telephone, gas, water, sewer, etc) with the appropriate utility provider before construction begins and at no additional cost to the
- All existing sanitary sewer manhole tops, water valve boxes, meters, storm sewers, or other related appurtenances shall be adjusted to finish grade by contractor at no additional
- 20. When project is complete, clean and polish glass, hardware, and other such items with factory finishes. Remove all dust with treated dust clithes or vacuum cleaners. Waste and refuse caused by the work shall be removed from premises and disposed of by contractor. Clean site at end of project. Remove dust, debris, oils, stains, fingerprints, and labels from exposed surfaces, including glazing.
- Furniture is for reference only, Furniture is not in project scope. Furniture, fixtures and equipment (FFE), if required, will be submitted in a separate design package.
- 22. Do not scale drawings for field layout. Contact architect if dimensions are needed and cannot be found in drawing set.
- 23. Floor plan dimensions taken from face of stud or centerline of stud / column unless otherwise noted. "Clear" refers to dimension between faces of finish surfaces. "EQ" or "Equal" indicates dimension to match adjacent. Lettered dimensions (A.B,C,D,ETC) indicate dimension to match opposite or remote (matching letter) dimension. "+/-" indicate: ximate dimension based on field consition or flexible dimension that can be adjusted
- 24. All dimensions on reflected ceiling / lighting plans are clear dimensions
- 25. These drawings are accompanied by the Project Manual.



SITE / VICINITY PLAN

OWNER

Soniat Holdings, LLC.

1133 Chartres St.

New Orleans, LA 70116

Albert Architecture and Urban Design, apllc

ARCHITECT

Richard Albert 3221 Tulane Avenue New Orleans, LA 70119 504.827.0056

INTERIOR DESIGNER

Ken Fulk

310 Seventh St. San Francisco, CA 94103 415.285.1164

GENERAL CONTRACTOR

Entablature

8438 Oak St., Suite C New Orleans, LA 70118 504.322.3822

MECHANICAL

Albert Engineering

Michael Leitzinger 3221 Tulane Avenue New Orleans, LA 70119 504.827.0056

ELECTRICAL

King Consulting Engineering, LLC

Kerwyn King P.O. Box 870398 504.399.1141

SONIAT HOUSE

PHASE 1

SONIAT HOLDINGS, LLC. 1130, 1133-1137 CHARTRES ST. NEW ORLEANS, LA 70116

PERMIT SET

EXTERIOR GATE/DOOR DETAILS

ELEVATION OF ROOF PENETRATIONS

VCC STANDARD DETAILS- IRON BALCONY AND GATES

02.07.22

DRAWING INDEX

A-5.10	ROOF JACKS / MECH PENETRATIONS		
		ID-1.00	INTERIOR FINISH SCHEDULE
64-0.00	COVER SHEET	ID-1.01	WALL TYPES
G-0.01	INFORMATION SHEET	ID-1.02	INTERIOR FINISH KEY PLAN
G-0.02	WALL FIXTURE MOUNTING AND ABA STANDARDS	ID-1.03	INTERIOR FINISH KEY PLAN
640.08	SURVEY	ID-1.04	INTERIOR FINISH KEY PLAN
G-0.04	WALL TYPES	E3-1.05	INTERIOR FINISH KEY PLAN
LS-1.00	LIFE SAFETY - FIRST FLOOR	ID-1.06	INTERIOR FINISH KEY PLAN
LS-1.01	LIFE SAFETY - SECOND FLOOR		
LS-1.02	LIFE SAFETY - THIRD FLOOR	M-0.01	HVAC CENERAL NOTES AND SCHEDULES
		M-0.02	HVAC SCHEDULES
D-1.00	INTERIOR DEMO-FIRST FLOOR- 1133-1137 CHARTRES	M-1.01	FIRST FLOOR PLAN - 1133-1137 CHARTRES
D-1.01	INTERIOR DEMO-FIRST FLOOR- 1130 CHARTRES	M-1.02	FIRST FLOOR HVAC - 1130 CHARTRES
D-1.02	INTERIOR DEMO-SECOND FLOOR- 1133-1137 CHARTRES	M-1.03	SECOND FLOOR HVAC - 1133-1137 CHARTRE
D-1.03	INTERIOR DEMO-SECOND FLOOR: 1130 CHARTRES	M-1.04	SECOND FLOOR HWAC-1130 CHARTRES
D-1.04	INTERIOR DEMO-THIRD FLOOR-1133-1137 CHARTRES	M-1,06	THIRD FLOOR HVAC- 1133-1137 CHARTRES
		M-1.06	ROOF HVAC PLAN - 1133-1137 CHARTRES
A-1.00	SITE PLAN	M-1.07	ROCE HVAC PLAN- 1130 CHARTRES
A.1.01	FIRST FLOOR PLAN 1133 1137 CHARTRES STREET	M-2.01	HVAC DETAILS
A-1.02	FIRST FLOOR PLAN - 1130 CHARTRES	M-2.02	HVAC DETAILS
A-1.00	SECOND FLOOR PLAN - 1133 - 1137 CHARTRES	M-3.01	MUCHANICAL RISURS
A-1.04	SECOND FLOOR PLAN - 1130 CHARTRES	M-3.02	MECHANICAL RISERS
A-1.06	THIRD FLOOR PLAN - 1133 - 1137 CHARTRES		
A-1.06	RDOF PLAN	b-0.01	ELECTRICAL GENERAL NOTES
A-1.09	FIRST FLOOR PLAN - RCP - 1133-1137 CHARTRES	E-1.01	FIRST FLOOR ELECTRICAL PLAN 1133-1137 C
A-1.10	FIRST FLOOR PLAN - RCP - 1130 CHARTRES	E-1.02	FIRST FLOOR ELECTRICAL PLAN 1130 CHART
A-1.11	SECOND FLOOR PLAN - RCP - 1133-1137	E-1.03	SECOND FLOOR ELECTRICAL PLAN 1133-113
A-1.12	SECOND FLOOR PLAN - RCF - 1130		CHARTRES
A-1.13	THIRD FLOOR PLAN - RCP - 1133-1137	E-1.04	SECOND FLOOR ELECTRICAL PLAN 1138 CH
A-2.00	EXTERIOR ELEVATIONS	E-1.06	THIRD FLOOR ELECTRICAL PLAN 1133-1137 (
A-3.00	SECTIONS	E-1.06	ROOF ELECTRICAL PLAN 1133-1137 CHARTRI
A-3.01	SECTIONS 2	E-1.07	ROOF ELECTRICAL PLAN 1130 CHARTRES
A-3.02	SECTIONS 3	E-2.01	ELECTRICAL RISER DIAGRAM AND DETAILS
A-5.00	TPO BOOF DETAILS		
A-5.01	RDOF DETAILS	P-0.01	PLUMBING GENERAL NOTES AND SCHEDULE
A-5.02	VCC STANDARD DETAILS - BRICK AND MORTAR	P-1.00	UNDERGROUND PLUMBING 1135-137 CHAR
A-5.03	VCC STANDARD DETAILS, SHUTTERS	P-1.01	UNDERGROUND PLUMBING 1130 CHARTRES
A-5.04	VCC STANDARD DETAILS - DORMER, WINDOWS &	P-1.02	FIRST FLOOR PLUMBING- 1133-1137 CHARTE

P-1.06 P-2.00 P-2.01 P-3.00 P-3.01

Drawn by:	
Checked by:	
Interior Demolition Set	08.13
Permit Set	09.23
Revised Permit Set	11.05
Revised Demoktion Set	12.16
Permit Revisions	61.27

COVER SHEET



02.07.22

SONIAT HOUSE

NEW ORLEANS, LA 70116

Project No. AA2109

1130, 1133-1137 CHARTRES STREET

ALBERT

ARCHITECTURE

Page 159 of 288

This drawing is copyrighted and is the sole properly of Albert Architecture & Uthan Design apile. Any use or reproduction of this chawing or the information curationals ben's without the written permission of Albert Architecture & Uthan Design apile is prohibited, all rights reserved.

3221 Tulane Avenue New Orleans, LA 70119 504 827 0056

Permit Bevisions

G-0.00

1135 Chartres

@ 2022 Albert Architecture & Urban Design aplic

PLUMBING GENERAL NOTES AND SCHEDULES

FIRST FLOOR PLUMBING- 1130 CHARTRES


SECOND FLOOR PLUMBING: 1130 CHARTRES


THIRD FLOOR PLUMBING- 1133-1137 CHARTRES PLUMBING DITAILS PLUMBING DETAILS

PLUMBING ISOMETRIC PLAN

UNDERGROUND PLUMBING 1135/157 CHARTISTS UNDERGROUND PLUMBING 1130 CHARTRES FIRST FLOOR PLUMBING- 1133-1137 CHARTRE

SECOND FLOOR PLUMBING-1133-1137 CHARTRES






VCC Architectural Committee

February 22, 2022






Interior Demolition Set


D-1.04

INTERIOR DEMO-THIRD FLOOR-1133-1137



1135 Chartres

© 2022 Albert Architecture & Urban Design splic





2 ROOF PLAN - 1133-1135 DEMO D-1.05 1/8" = 1'-0"

CLARIFICATION OF RENOVATION GRAPHICS		
	PERTAINING TO SITE PLAN	
	PROPERTY LINE	
	BUILDING - IN SCOPE	
	BUILDING - NOT IN SCOPE	



Abert / Page 10164 of 288
S221 Tulana Avanua
New Criseras I JA 20119
504 827 6056





SONIAT HOUSE

1130, 1133-1137 CHARTRES STRE NEW ORLEANS, LA 70116

Project No. AA2109


Drawn by:







A-1.00

© 2022 Albert Architecture & Urban Design aplic









18D FLOOR PLAN-13 - 1137 CHARTRES


22, 2022

ALBEKI

















ALBERT ARCHITECTURE

Page 171 of 288

3221 Tulane Avenue New Orleans, LA 701 19 504.827.0056

This drawing is copyrighted and is the sole property of Albert Architecture 8, this in Death Architecture 8, this in Death and the Architecture 1, the architecture of the Architecture 1, the Architecture 1,

SONIAT HOUSE

1130, 1133-1137 CHARTRES STREET NEW ORLEANS, LA 70116

Project No. AA2109

02.07.22 Permit Set Revised Permit Set


A-1.13



© 2022 Albert Architecture & Urban Design aplic









3/16" = 1'-0"

SONIAT HOUSE 1130, 1133-1137 CHARTRES STREI NEW ORLEANS, LA 70116

Project No. AA2109

02.07.22

Interior Demolition Set

ALBERT

This thowing is onesyighted and in the sole property of Albert Architecture & Uthan Design agic. Any use or reproduction of this drawing or the information contained herein without the writest permission of Albert Architecture & Uthan Design apric is prohibited, all rights reserved.

Page 173 of 288 521 Talane Avenue New Orleans, LA 78119 164.627.0016

A-3.00



09.23.21 11.05.21

1135 Chartres

© 2022 Albert Architecture & Urban Design aplic



NOTE:


REFERENCE GENERAL VCC GUIDELINE SHEETS (A-5.02 - A-5.05) FOR APPROVED STANDARD DETAILS. CONTACT ARCHITECT IF APPLICABILITY OF DETAIL IS IN QUESTION.




SECTION / REAR ELEVATION 3 - 1133-1137 CHARTRES


3/16" = 1'-0"








1135 Chartres
VCC Architectural Committee



2 ELEVATION AT HISTORIC DOOR- 1133-1137 CHARTRES



INFILL AT HISTORIC DOOR- 1133-1137 CHARTRES

© 2022 Albert Architecture & Urban Design aplic

ALBERT

Page 175 of 288

3221 Tulane Avenue New Orleans, LA 70119 504 827 0056

This drawing is exceptigited and is the sole property of Albert Architecture & Inthan Design, edit. Any use or reproduction of this drawing or the information contained benefine whose the estimation contained benefine whose the william permission of Albert Architecture & Urban Design adilc is prohibited, all rights reserved.

SONIAT HOUSE


1130, 1133-1137 CHARTRES STREET NEW ORLEANS, LA 70116

Project No. AA2109

Interior Demolition Set	Drawn by:	
Permit Set 09.23 Besided Permit Set 11.05 Revised Demoition Set 12.16 Paumit Revision 01.27	Checked by:	
	Interior Demolition Set	08.13.
Revised Demolition Set 12.16. Permit Bevision x 01.27.	Permit Set	09.23.
Permit Besisiums 01.27	Revised Permit Set	11.05
	Revised Demolition Set	12.16.
Permit Revisions 02.27.	Permit Bevisiums	01.27
	Permit Revisions	02.27.


A-4.00

ENLARGED PLAN/DETAILS




DISTRICT AND THE ADDRESS CONTINUOUS CORPERATING, COPING TO SE CONTINUOUS CONT

SECTION AT TPO ROOF AT EXISTING PARAPET - 1130 CHARTRES



3 SECTION THRU INTERNAL GUTTER - 1133-1137 CHARTRES

PREFABRICATED ROOF HATCH SYSTEM TREATED CANT STRIP SEE STRUCTURAL FOR FRAMING OF OPENING STEEL LADDER, PROVIDE SHOP DRAWINGS SECTION AT ROOF HATCH



SECTION THRU NEW SKYLIGHT

1180, 1183-1187 CHARTRES STREET
NEW ORLEANS, LA 70116
Project No. AA2109

02.07.22

Describy AP
Chestafty AR
Interior Describios Set 08.1524
Revised Ferrir Set 12.2521
Revised Cempition Set 12.2621
Parmit Reviside Cempition Set 17.2527
Parmit Reviside 07.27.727
Parmit Reviside 07.27.727

SONIAT HOUSE

ALBERT

ARCHITECTURE

Abert Architecture & Urban Design apilo

3221 Tubina Avenue
New Orleans, LA 20119


304-827 2009


This drawing is copyrighted and is the sole property of Albart. Architecture & Uthan Design agic. Any use or reproduction of this drawing or the information contained nerve without the setting parmission of Albart Architecture. & Uthan Design apile is prohibited, all rights reserved.

A-5.01

© 2022 Albert Architecture & Urban Design apile ROOF DE


ROOF DETAILS






INTERIOR SECURITY GATE- 1133-1137 CHARTRES


EXTENDR STEEL GATE CESION BASED ON VCC STANDARD DETALS. GATE LEEVATIONS ARE RELICE PROPOSED AND APPROPRIATIONS. TO BE DETERMINED BY AN PROPOSED COMPAGUATION FOR BOTH 1519 & 1133 CHARLES ALLY PROPOSED COMPAGUATION FOR BOTH 1519 & 1133 CHARLES ALLY PROPOSED VIDIOUS DOORS TO MAICH EXISTING AND NEW VIRGIDITIES OF SERIOD.




SECURITY GATE AT 1133-1137 CHARTRES












1130 CHARTRES STREET ENTRY GATE
3/4" = 1'-0"





Albert Architecture & Urban Design aplic 3221 Tulane Avenue New Orleans, LA 70119 504 827.0056

This drawing is copyrighted and is the sole property of Albart Architecture 2. Lithran Design aglic. Any use or reproduction of this drawing or the information contained hereit without the written permission of Albart Architecture. A Lithran Besign aglic is prohibited, all lights reaszwed.

SONIAT HOUSE

1130, 1133-1137 CHARTRES STREET NEW ORLEANS, LA 70116

Project No. AA2109

02.07.22

Checked by

A-5.08



1135 Chartres

Page 179 of 288

Albert Architecture & Urban Design apilo 3221 Tulane Avenue New Orleans, LA 70119 504.827.0056


This drawing is cognificated and is the sole property of Albert Architecture & Uthan Begg, agin, Any use or reproduction of this drawing or the information contributed herein abbout the witten permission of Albert Architecture & Uthan Design agin to prohibited, all rights reserved.




A-5.09

ELEVATION OF ROOF PENETRATIONS


© 2022 Albert Architecture & Urban Design apilic







1135 Chartres

09.23.21 11.05.21









VCC Architectural Committee

February 22, 2022
























































































226 Bourbon













226 Bourbon







226 Bourbon





Spun Aluminum Model GRSI/GRSR/GRSF





Construction Features

When you buy a Greenheck gravity ventilator, you receive a ventilator with the industry's best performance and durability for intake (model GRSI) or relief (model GRSR) for natural gravity or positive pressure systems. Exceptional low silhouette design and construction features make this unit a rugged, efficient, and economical air inlet or outlet.

- Broadest performance in the industry, up to 18,400 cfm (31,300 m³/hr)
- Most advanced weather protection of any ventilator in its class
- Greenheck subjects these products to extensive life testing, ensuring the ventilator will provide years of reliable performance

- All aluminum exterior for corrosion-resistant construction
- Integral birdscreen to prevent the entry of birds and/or small objects
- Built-in curb cap with pre-punched holes for easy attachment to roof curbs
- Optional built-in flashing flange (model GRSF) with pre-punched holes for quick and easy installations without a roof curb.

Use the GRS with the following accessories:

Gravity or motorized dampers to ensure weather tightness.


Prefab curbs to reduce installation time.


Protective coatings to extend the life of the unit or blend its color with other equipment.



					Dim	ensio	ns			
Model Size	Α	В	С	D	Е	F	Damper Size	Curb Thickness	Shroud Thickness	Unit Weight
8	19 (483)	20½ (521)	7¼ (184)	1½ (38)	20¼ (514)	8¼ (210)	8 x 8 (203 x 203)	0.051 (1.3)	0.051 (1.3)	7 (3)
10	19 (483)	20½ (521)	7¾ (197)	2 (51)	20¼ (514)	10¼ (260)	10 x 10 (254 x 254)	0.051 (1.3)	0.051 (1.3)	8 (4)
12	22 (559)	29 (737)	10 (254)	3½ (89)	23¼ (591)	12¼ (311)	12 x 12 (305 x 305)	0.064	0.064	10 (5)
15	22 (559)	29 (737)	10 (254)	3½ (89)	23¼ (591)	14¼ (362)	16 x 16 (406 x 406)	0.064 (1.6)	0.064 (1.6)	13 (6)
16	26 (660)	29 (737)	11 (279)	4¼ (108)	27¼ (692)	16¼ (413)	16 x 16 (406 x 406)	0.064	0.064 (1.6)	16 (7)
18	30 (762)	35½ (902)	9¼ (248)	1% (44)	31¼ (794)	20¼ (514)	18 x 18 (457 x 457)	0.064	0.064	19 (9)
20	30 (762)	35½ (902)	11½ (286)	3¼ (95)	31¼ (794)	20¼ (514)	18 x 18 (457 x 457)	0.064	0.064	24 (11)
24	34 (864)	38¼ (972)	11 (279)	4 (102)	35¼ (895)	24½ (622)	24 x 24 (610 x 610)	0.064 (1.6)	0.064	29 (13)
30	40 (1016)	48 (1219)	18¼ (476)	5½ (138)	-	30½ (775)	30 x 30 (762 x 762)	0.064	0.064	35 (16)
36	46 (1168)	56% (1441)	21¼ (540)	10 (254)	-	36½ (927)	36 x 36 (914 x 914)	0.064	0.080 (2.0)	45 (20)
42	52 (1321)	63¼ (1607)	24¼ (616)	11¼ (286)	-	42½ (1089)	42 x 42 (1067 x 1067)	0.064	0.080	60 (27)
48	58 (1473)	72 (1829)	261/4	11¼ (286)	-	48½ (1232)	48 x 48 (1219 x 1219)	0.064	0.080	80 (36)

All dimensions are in inches (millimeters) and the weight in pounds (kilograms). NOTE: Sizes GRS-8 through 24 have a one-piece cover and shroud. Access is gained through the removal of screws. Sizes GRS-30 through 48 have a removable over, separate from the shroud, to facilitate maintenance and servicing of damped and the size of the size o














AWL.70





SPECIFICATIONS

Material

Finish

Machined aluminum with glass lens
Aluminium: Brushed aluminum with Ships with Mini Junction by by and stainless steel fasteners.

clear powdercoat. Matte black or Lumenart remote driver. Optional white Tiger Drylac powdercoat. Electrical

ETL wet location listed.

ASC for mounting driver in 4-0 octagon box. Total Luminaire wattage 14.48w 860 lm

Fixture	LED	Voltage	Finishes	Option
AWL.70	3000k	UNV	Aluminium	ASC
			Black	
			White	

LumenArt, Ltd. 3333 W. 47th St., Chicago, IL 60632 Phone 773-254-0744 Fax 773-254-0767 www.lumenart.com









Figure 28. 6, 7.5 ton condensing unit, dual compressor, microchannel



Dimensions

4TTA3 Outline Drawing NOTE: ALL DIMENSIONS ARE IN MM (INCHES)





	MODELS	BASE	FIG.	A	В	С	D	Е	F	G	Н	J	K	١.
\rightarrow	4TTA3036B	3	1	733 (28-3/4)	829 (32-5/8)	756 (29-3/4)	3/4	3/8	137 (5-3/8)	79 (3-1/8)	197 (7-3/4)	60 (2-3/8)	508 (20)	\leq
	4TTA3042D	4	1	741 (29-1/8)	946 (37-1/4)	870 (34-1/4)	3/4	3/8	152 (6)	98 (3-7/8)	219 (8-5/8)	86 (3-3/8)	508 (20)	
	4TTA3048D	4	1	741 (29-1/8)	946 (37-1/4)	870 (34-1/4)	7/8	3/8	152 (6)	98 (3-7/8)	219 (8-5/8)	86 (3-3/8)	508 (20)	ĺ
	4TTA3060D	4	1	943 (37-1/8)	946 (37-1/4)	870 (34-1/4)	7/8	3/8	152 (6)	98 (3-7/8)	219 (8-5/8)	86 (3-3/8)	508 (20)	ĺ

CITYMULTI®

6-TON TURYP0723AN40A(N/B)





Job Name:

System Reference:

208/230V OUTDOOR VRF HEAT RECOVERY SYSTEM



RYP0723AN40AN
RYP0723AN40AB

Date:

ACCESSORIES

ACCESSORIES	
BC Controller (Required)	for details see BC Controller Submitta
Joint Kit	for details see Pipe Accessories Submitt
Panel Heater Kit	for details see Panel Heater Kit Submitt
Snow/Hail Guards Kit	for details see Snow/Hail Guards Kit Submitt

	Specifications		System		
	Unit Type		TURYP0723AN40A(N/B)		
Cooling Capacity (Nominal)		BTU/H	72,000		
Heating Capacity (Nominal)		BTU/H	80,000		
	Cooling ²	°F [°C]	23~126 [-5.0~52.0]		
Guaranteed Operating Range¹	Heating ³	°F [°C]	-4~60 [-20.0~15.5]		
Extended Operating Range	Heating	°F [°C]	-18~60 [-18.0~15.5]		
External Dimensions (H x W x D)		In. [mm]	71-5/8 x 36-1/4 x 29-5/32 [1,818 x 920 x 740]		
Net Weight		Lbs. [kg]	519 [235]		
External Finish			Pre-coated galvanized steel sheet (+powder coating for -BS type) <munsell 1="" 5y="" 8=""></munsell>		
Electrical Power Requirements	Voltage, Phase, Hertz, Power	Tolerance	208/230V, 3-phase, 60 Hz, ±10%		
Minimum Circuit Ampacity		A	24.0/22.0		
Maximum Overcurrent Protection		A	40/35		
Recommended Fuse Size		A	30/30		
Recommended Minimum Wire Size		AWG [mm]	10/10 [5.3/5.3]		
SCCR		kΑ	5		
	Liquid (High Pressure)	In. [mm]	5/8 [15.88] Brazed		
Refrigerant Piping Diameter	Gas (Low Pressure)	In. [mm]	3/4 [19.06] Brazed		
Max. Total Refrigerant Line Length		Ft.	1804		
Max. Refrigerant Line Length (Between ODU & IDU)	Ft.	541		
Max. Control Wiring Length		Ft.	1640		
	Total Capacity		50.0~150.0% of outdoor unit capacity		
ndoor Unit Connectable	Model/Quantity		P05~P96/1.0~18.0		
Sound Pressure Levels		dB(A)	56.5-58.0		
Sound Power Levels		dB(A)	75.5/77.0		
	Type x Quantity		Propeller fan x 1		
	Airflow Rate	CFM	6000		
FAN ⁴	External Static Pressure	In. WG	Selectable; 0.00, 0.12, 0.24, 0.32 In, WG; factory set to 0 In, WG		
Compressor Operating Range			15.0% to 100.0%		
Compressor	Type x Quantity		Inverter scroll hermetic compressor x 1		
Refrigerant	Type x Original Charge		R410A x 11 lbs + 7.0 oz [5.2 kg]		
	High Pressure Protection		High pressure sensor, High pressure switch at 4.15 MPa (601 psi)		
Protection Devices	Inverter Circuit (Comp./Fan)		Over-heat protection, Over-current protection		
	Fan Motor		Over-current protection		
	EER		13.1/14.7		
NIDI Delines (Dusted Blood dusted)	IEER		23.8/29.2		
AHRI Ratings (Ducted/Non-ducted)	COP		3.76/4.09		
	SCHE		25.9/25.5		

Nominal cooling conditions (Test conditions are based on AHRI 1230) Indoor: 80°FD.B./67°FW.B. (26.7°CD.B./19.4°CW.B.), Outdoor: 95°FD.B. (35°CD.B.) Nominal heating conditions (Test conditions are based on AHRI 1230) Indoor: 70°FD.B. (21.1°CD.B.), Outdoor: 47°FD.B./43°FW.B. (8.3°CD.B./6.1°CW.B.) 'Harsh weather environments may demand performance enhancing equipment. Ask your Mitsubishi Electric representative for more details about your region

²For details on extended cooling operation range down to -10" F DB, see Low Ambient Kit Submittal 3When applying product below -4°F, consult your design engineer for cold climate application best practices, including the use of a backup source for heating

*Unit will continue to operate in extended operating range, but capacity is not guaranteed








Figure 25. Cooling and gas/electric — 10 tons high efficiency



INTELLISTRAND CABLE LIGHT

KEY FEATURES

- Low voltage cable light for indoor / outdoor lighting applications, perfect for festoon mounting, taught or swayed.
- 16 gauge conductive cable with factory attached sockets.
- Lamp spacing available in 12" OC and 24" OC.
- · Flat base can be easily mounted against a wall or ridged surface.


Max continuous length: 50' max per run (12" OC)
 100' max per run (24" OC)

Multiple dimming options available, see power supply selections.






DIMENSIONAL DRAWING



INSTALLATION EXAMPLES



DETAILS

Spacing 12" or 24" OC Socket Spacing

Color Temp 2300K

Wattage 1.5W per socket

Installation Attach to aircraft cable (sold seperately) and to be secured with

cable ties (provided by others). Optional cable wrap encases aircraft cable and Intellistrand cable for a clean one wire look

(see page 3).

leight 0.25Lbs/socket

Power Supply Listed Class 2 output, 24 VDC power supply required

IP Rating IP

ertifications cETLus Class 2 Wet Listed 4007019

Tested in accordance with LM-79-08 Energy efficient for California installations.

5 year warranty

Aircraft Cable FIX Model

FIXTURE DATA


Model	Efficacy* Lm/Wt	Lm/Bulb	Wt/ Globe
2300K	45*	67	1.5



SUSPENDED DECORATIVE STRINGLIGHT SYSTEMS







SOCKET, WIRE & CABLE DETAILS

Decostrings are a perfect accent lighting solution to add a personal ambience to patios, courtyards, atriums, restaurants, amusement parks and any open area. The "festoon" lighting system is typically strung between two anchorage points with optional intermediary support and electrically fed from one end. The sockets can be either symmetrically spaced or randomly spaced to suit the application. Optional shades, guards and lenses complete the architectual design.

SPECIFICATIONS

LAMPHOLDER Black phenolic, medium base UL weatherproof with hook for optional mounting.

POWER CORD 12/2 G. Black flexible duplex cable, UV rated for extended outdoor use.

SUPPORT CABLE 3/32" SS aircraft catenary cable supports the system, 980# test. Heavier cable available.

TERMINATION KITS Heavy duty stainless steel hardware available.

LAMPS Wet location rated LED and incandescent medium base A, G or S style lamps.

DIMMING Dimmable to 10% with ELV trailing edge type dimmers.

VOLTAGE 120V system (1920 watts max load). No driver or transformer required.

ACCESSORIES Optional brass, aluminum and acrylic shades. Consult factory for custom shades.

PHOTOMETRY Bare lamp and shielded "BUG" rated .IES files available.

ETL listed for permenant damp or wet installations. (1) 2001431 CERTIFICATION







(SEE PAGE 6)

PART NUMBER





PRIMUS

LED FILAMENT STYLE LAMPS



S14-24/150 - 24K,1.5W, 150L, CLEAR S14-27/150 - 27K,1.5W, 150L, CLEAR

WHITE OR FROSTED - CONSULT FACTORY



VINTAGE LED LAMPS CONSULT FACTORY



G16.5

G16,5F-24/325 - 24K, 3.5W, 325L, CLEAR G16.5F-27/325 - 27K, 3.5W, 325L, CLEAR

G16.5F-24/200 - 24K, 2W, 200L, CLEAR G16.5F-27/200 - 27K, 2W, 200L, CLEAR

WHITE OR FROSTED - CONSULT FACTORY



A15 & A19 CONSULT FACTORY



S14 VARIOUS COLORS CONSULT FACTORY



CONSULT FACTORY

* ADD "SC" SUFFIX FOR SILICONE COATING (FOOD SERVICE)

* SEE INDIVIDUAL DATA SHEETS FOR COMPLETE LAMP SPECIFICATIONS

* LED LAMPS SPECIFICALLY WET RATED AND DIM DOWN TO 10% WITH A TRAILING EDGE (ELV) DIMMER.

INCANDESCENT LAMPS (OPTIONAL)






LH-C G16.5 CLEAR 120V 25W G16.5 WHITE 120V 25W











7" W X 3" H CONE SHADE

10" W X 3" H CONE SHADE

12" W X 4" H CONE SHADE

DSC7

DSC10

DSC12

FINISH:

PROVIDES OVOYO BLIG BATING

FACTORY INSTALLED

DSRW4

FINISH:

DECOSTRING SHADES & GUARDS


PRIMUS

Page 217 of 288

WET RATED LED LAMPS FOR DECOSTRING & MARQUIS







6 OZ 9 OZ 18 OZ SHOWN: AGED BRASS (AB)

DSH4 4" W X 1 7/8" H HAT SHADE 2 OZ DSH6 6" W X 2 1/4" H HAT SHADE 4 OZ DSH8 8" W X 2 3/4" H HAT SHADE 6 OZ FINISH: ACID ETCHED BRASS OR POWDER COAT

4" W X 1 7/8" H RADIAL WAVE SHADE

ACID ETCHED BRASS OR POWDER COAT



RADIAL WAVE SHADE 4 OZ 8" W X 2 3/4" H RADIAL WAVE SHADE ACID ETCHED BRASS OR POWDER COAT



SHOWN: POWDER COAT BLACK (PCB)

DST4P 4" W X 6" H PERFORATED TUBE SHADE 11 OZ DST6P 6" W X 8" H PERFORATED TUBE SHADE 22 OZ FINISH: ACID ETCHED BRASS OR POWDER COAT





SHOWN: RAW (RB)

4" W X 6" H WIRE CAGE TUBE DST4C 9 OZ 6" W X 8" H WIRE CAGE TUBE 15 OZ ACID ETCHED BRASS OR POWDER COAT





6" W X 5 1/8" H

ROUND SHADE WITH GUARD

ACID ETCHED BRASS OR POWDER COAT

* DELETE "G" FOR NO GUARD.



SHOWN: CUSTOM TEXTURED BRONZE

FACTORY INSTALLED

DSWG

FINISH:

3 7/8" W X 5 5/8" H WIRE GUARD

6 OZ

9 OZ

CAD PLATED OR POWDER COAT BLACK CAN BE USED WITH CONE SHADE DSC10, DSC12



3570 LEXINGTON AVE. EL MONTE, CA 91731 • PH. 626.442.4600 • primuslighting.com

SPECIFICATIONS

SOURCE Filament Style LED

Medium Base E26 BASE

LENS Clear Glass

VOLTAGE 120V - No Driver Required

DIMMING 100-10% with ELV Type Dimmer (Reverse Phase Cut)

25,000 Hours / 3 Year Limited Warranty LAMP LIFE

CSA-C-US Wet Location CERTIFICATION

PERFORMANCE

LED COLOR	WATTS	LUMENS	INCANDESCENT EQUIVALENT
WHITE 2400K	3.5	330	40 WATT
WHITE 2700K	3.5	350	40 WATT
WHITE 2400K	2	200	20 WATT
WHITE 2700K	2	200	20 WATT

PART NUMBER

PLED-G16.5F-3.5W 24K

(3.5W, 2400K, 325 LUMENS)

PLED-G16.5F-3.5W-27K

(3.5W, 2700K, 325 LUMENS)

PLED-G16.5F-2W-24K

(2W, 2400K, 200 LUMENS)


PLED-G16.5F-2W-27K

(2W, 2700K, 200 LUMENS)






634 Esplanade




634 Esplanade

VCC Architectural Committee



















634 Esplanade


































December 6, 2021

Andrea & Chip Register 634 Esplanade Ave New Orleans, LA 70116

To contract with

TECC ENTERPRISES LLC 2831 St Claude Ave

New Orleans, LA 70117

Property address

634 Esplanade Ave New Orleans, LA 70116

SCOPE OF WORK

From the street perspective, the left side of the house has a 40LF section that runs from the bump out to the end of the house which is about 4 ½ inches lower than the rest of the house (see engineer drawings) due to a previously failing foundation which has since been repaired by another contractor. A complication to this repair is that the kitchen floors and cabinets were previously installed level over unlevel structural supports. To remedy this, we will remove the siding to repair the wall framing and joists where necessary. Additionally, we will jack up this wall to be as close to plum as possible with the rest of the house. We endeavor to preserve the floors and cabinets as best we can.

The 2nd & 3rd floor framing has shifted as a result of the previously failing foundation. To remedy this, we will push/pull the 2nd and 3rd floor as close to plum as possible with the 1st floor, adding supports to hold framing in place as necessary. We will install new siding, caulk & paint. We will shim existing piers as needed for leveling. We will nail existing floor joists to existing sills to prevent future separation. We will repair cracked sheetrock or plaster that occurs from work being performed up to the allowance. Scope of work includes furnishing all materials, supervision, labor & equipment to perform the work per engineer's drawing.

Permit	\$2,500
Remove siding	15,500
Repair wall & floor framing	20,200
Jack up house back to its original position	21,500
Install new vapor barrier & siding	27,700
Prime, paint, & caulk new siding	19,200
Interior repair allowance	20,000
TOTAL	\$126,600

Payment schedule

(\$44,310) 35% contract signing PAID \$44,310 35% siding removed and new framing complete 30% completion

If necessary and with approval, sill replacement will cost \$100/LF, and joist replacement will cost \$120/joist.

PRICE EXCLUDES unforeseen conditions, including but not limited to plumbing; electrical; mechanical; duct work; tile, cabinet, or floor repairs; or, roof issues associated with this repair.

ACCEPTANCE OF THIS AGREEMENT is binding between TECC ENTERPRISES LLC and ANDREA & CHIP RECISTER upon written acceptance in the space provided below or upon the contractor commencing performance. Commencement of performance shall constitute the entire contract and be binding upon the parties hereto, there being no covenants, promises, warranties, agreements written or oral, expressed or implied, except as set forth herein.


RESPECTFULLY SUBMITTED by TECC ENTERPRISES LLC & TIM CLARK.

DATE 09 Dec 21


The above prices, specifications and conditions are satisfactory and hereby accepted. We, the undersigned, fully understand and agree to the terms and conditions as described in this document, and I hereby authorize TECC ENTERPRISES LLC to perform the work as specified in good faith.


DATE 10 PGC 21


































































KEYNOTES:

- 1 EXISTING ARATA/ENT TO BE REMOVED AND REPLACED WITH STANDING SEAM COPPEL
- REMOVE UNUSED CONDUIT AND PIPING. PAINT CONDUIT AND PIPING TO MATCH WALL
- 3. REPAIR VITRINE WINDOWS AND WOOD PANELS. NEW STANDING SEAM METAL ROOF TO MATCH EXISTING.
- REPAIR AND RE-INSTALL EXISTING PAINTED WOOD VERTICAL BOARD / STILE AND RAIL SHUTTERS, RE: ELEVATIONS FOR SPECIFIC REPAIR AT EACH OPENING.
- 4.1 NEW HINGE TO MATCH EXISTING.
- 4.2 REPLACE SHADED AREA OF SHUTTER WITH NEW PAINTED WOOD TO MATCH EXISTING.
- 5. REMOVE EXISTING GATE, NEW 3'-6' WIDE BEADED BOARD WOOD GATE. PER FRONT ELEVATION, MASONRY JAMBS TO REMAIN.
- 8. REMOVE EXISTING IRON GATE AND WOOD POSTS, NEW 3' WIDE BEADED BOARD WOOD GATE.
- REMOVE AND REPLACE WINDOW W/ NEW 6 OVER 8 DOUBLE-HUNG PAINTED WOOD WINDOW WITH TRUE DIVIDED LITES TO MATCH EXISTING IN
 EXISTING MASONRY OPENING, NEW PAINTED WOOD SHUTTERS WITH PAINTED CAST IRON STRAP HINGES.
- 8. EXISTING GAS METER. ENTERGY TO RAISE TO CLEAR 7'-6" FROM GRADE TO BOT OF METER
- 9. RETAIN EXISTING A/C'S AND PLATFORN
- SHIFT EXISTING AIC PLATFORM AND UNITS TOWARD ESPLANADE AVE. SIDE TO ALLOW FOR EXIT PASSAGEWAY THRU CANAL STREET SIDE ALLEYWAY.
- 11. REMOVE AND REPLACE EXISTING WOOD / GLASS DOORS AND SIDELITES TO MATCH EXISTING; TRANSOMS TO REMAIN
- 12. REMOVE VERTICAL BOARD WOOD. FENCE AND GATES; NEW 7-BOARD FENCE AND PAIR 3' GATES W/ PANIC EXIT HARDWARE, RE: 3/A2
- NEW ILLUMINATED EXIT SIGN, TYP
- 14. EXISTING COPPER PARAPET / COPING TO BE REMOVED AND REPLACED, TYP. EXISTING L-SHAPED FLASHING TO REMAIN.
- 15. EXISTING LIGHT FIXTURES TO BE REMOVED. NEW LIGHT FIXTURES CENTERED ON DOOR & WINDOW OPENINGS, TYP. RE: FIXTURE CUT SHEET 4/A2
- REMOVE FAI







RAZZOO BAR AND PATIO EXTERIOR MODIFICATIONS

511 Bourbon Street New Orleans, Louisiana 70130 LKHarm
A Professional
0288
New Orleans
G04.485.5670 Inst

LKHarmon Architects
A Professional Architectural Corporation
0828 Argunus Evulevand
New Orleans Louislona 70124
54.465.2970 Intermediblammunchitects.com

INDICATES AFE VAL DORAY IF POINTED ON A WASH'S SHETTS.

CCLS

W.C.C.


A

LKH#22215.2

GUELKHAFMONAN In LKH#2215.2


KEYNOTES:

- 1. EXISTING ABAT-VENT TO BE REMOVED AND REPLACED WITH STANDING SEAM COPPER.
- REMOVE UNUSED CONDUIT AND PIPING. PAINT CONDUIT AND PIPING TO MATCH WALL.
- 8. REPAIR VITRINE WINDOWS AND WOOD PANELS, NEW STANDING SEAM METAL ROOF TO MATCH EXISTING.
- 4. REPAIR AND RE-INSTALL EXISTING PAINTED WOOD VERTICAL BOARD / STILE AND RAIL SHUTTERS, RE: ELEVATIONS FOR SPECIFIC REPAIR AT EACH OPENING.
- 4.1 NEW HINGE TO MATCH EXISTING.
- .2 REPLACE SHADED AREA OF SHUTTER WITH NEW PAINTED WOOD TO MATCH EXISTING
- 5. REMOVE EXISTING GATE, NEW 3'-6" WIDE BEADED BOARD WOOD GATE PER FRONT ELEVATION, MASONRY JAMBS TO REMAIN.
- 8. REMOVE EXISTING IRON GATE AND WOOD POSTS. NEW 3' WIDE BEADED BOARD WOOD GATE.
- REMOVE AND REPLACE WINDOW W/ NEW 6 OVER 6 DOUBLE-HUNG PAINTED WOOD WINDOW WITH TRUE DIVIDED LITES TO MATCH EXISTING IN EXISTING MASONRY OPENING; NEW PAINTED WOOD SHUTTERS WITH PAINTED CAST IRON STRAP HINGES.
- 8. EXISTING GAS METER. ENTERGY TO RAISE TO CLEAR 7'-6" FROM GRADE TO BOT OF METER.
- RETAIN EXISTING A/C'S AND PLATFORM
- SHIFT EXISTING A/C PLATFORM AND UNITS TOWARD ESPLANADE AVE. SIDE TO ALLOW FOR EXIT PASSAGEWAY THRU CANAL STREET SIDE ALLEYWAY.
- 11. REMOVE AND REPLACE EXISTING WOOD / GLASS DOORS AND SIDELITES TO MATCH EXISTING; TRANSOMS TO REMAIN
- 2. REMOVE VERTICAL BOARD WOOD FENCE AND GATES; NEW 7-BOARD FENCE AND PAIR 3' GATES W/ PANIC EXIT HARDWARE, RE: 3/A2
- 3. NEW ILLUMINATED EXIT SIGN, TYP.
- 14. EXISTING COPPER PARAPET / COPING TO BE REMOVED AND REPLACED, TYP. EXISTING L-SHAPED FLASHING TO REMAIN.
- 15. EXISTING LIGHT FIXTURES TO BE REMOVED. NEW LIGHT FIXTURES CENTERED ON DOOR & WINDOW OPENINGS, TYP. RE: FIXTURE CUT SHEET 4/A2
- REMOVE FAN.







- 1. EXISTING ABAT-VENT TO BE REMOVED AND REPLACED WITH STANDING SEAM COPPER.
- 2. REMOVE UNUSED CONDUIT AND PIPING. PAINT CONDUIT AND PIPING TO MATCH WALL.
- REPAIR VITRINE WINDOWS AND WOOD PANELS. NEW STANDING SEAM METAL ROOF TO MATCH EXISTING.
- 4. REPAIR AND RE-INSTALL EXISTING PAINTED WOOD VERTICAL BOARD / STILE AND RAIL SHUTTERS, RE: ELEVATIONS FOR SPECIFIC REPAIR AT EACH
- 4.1 NEW HINGE TO MATCH EXISTING.
- 4.2 REPLACE SHADED AREA OF SHUTTER WITH NEW PAINTED WOOD TO MATCH EXISTING.
- REMOVE EXISTING GATE, NEW 3'-6' WIDE BEADED BOARD WOOD GATE PER FRONT ELEVATION, MASONRY JAMBS TO REMAIN.
- REMOVE EXISTING IRON GATE AND WOOD POSTS, NEW 3' WIDE BEADED BOARD WOOD GATE.
- REMOVE AND REPLACE WINDOW WINEW 6 OVER 6 DOUBLE-HUNG PAINTED WOOD WINDOW WITH TRUE DIVIDED LITES TO MATCH EXISTING IN
 EXISTING MASONRY OPENING; NEW PAINTED WOOD SHUTTERS WITH PAINTED CAST IRON STRAP HINGES.
- 8. EXISTING GAS METER. ENTERGY TO RAISE TO CLEAR 7'-6" FROM GRADE TO BOT OF METER.
- 9. RETAIN EXISTING A/C'S AND PLATFORM
- 10. SHIFT EXISTING A/C PLATFORM AND UNITS TOWARD ESPLANADE AVE. SIDE TO ALLOW FOR EXIT PASSAGEWAY THRU CANAL STREET SIDE
- 11. REMOVE AND REPLACE EXISTING WOOD / GLASS DOORS AND SIDELITES TO MATCH EXISTING; TRANSOMS TO REMAIN
- 12. REMOVE VERTICAL BOARD WOOD FENCE AND GATES; NEW 7-BOARD FENCE AND PAIR 3' GATES W/ PANIC EXIT HARDWARE, RE: 3/A2
- 13 NEW ILLUMINATED EXIT SIGN TVI
- 14. EXISTING COPPER PARAPET / COPING TO BE REMOVED AND REPLACED, TYP. EXISTING L-SHAPED FLASHING TO REMAIN.
- 15. EXISTING LIGHT FIXTURES TO BE REMOVED. NEW LIGHT FIXTURES CENTERED ON DOOR & WINDOW OPENINGS, TYP. RE: FIXTURE CUT SHEET 4/A2
- REMOVE FAN.











RAZZOO BAR AND PATIO EXTERIOR MODIFICATIONS


511 Bourbon Street New Orleans, Louisiana 70130 LKHarmon Architects
A Professional Architectural Corporation
6338 Arconno Boulevana
New Orleans Louistans 70124
6016 3570 Autonomosibleramonatifetero-iva


TED ARE VALID ONLY IF FRACTO ON 24-30° SLETTS
12-, 17-, 2021
V.C.C.

A 2


LKH#2215.2




































































































Star: is original loatern with chain. Height is 24" tall Main Les Lantern Size is 24" Tall & 14" Wide (original)
with 2ft chain.


D- circle- Same length & dimensions as original lanterns - but newly purchased



VCC Architectural Committee







835-39 Decatur























835-39 Decatur



835-39 Decatur – Stop Work Order Place 10/26/16






835-39 Decatur – ATM and Signage 11/15/16





835-39 Decatur – Additional Signage 12/12/16
































835-39 Decatur



SCALE: 1/4" = 1'-0"

835-39 Decatur

Page 288 of 288